




WTC MACHINERY Diseñado para funcionar. Construido para durar.

WTC Machinery es líder mundial en el diseño y construcción de maquinaria y herramientas para instalaciones de reparación de equipos pesados.

MPP150 Prensa Pin Portátil

Descripción general

WTC Machinery rango media MPP150 prensa de pasadores portátil con una fuerza de prensado de hasta 150 toneladas, es una herramienta robusta capaz de manejar los trabajos más exigentes. Esta prensa de pasadores cuenta con un diseño de tirantes que facilita el mantenimiento de equipos de construcción o minería de mayor tamaño y es ideal para excavadoras y bulldozers de hasta Caterpillar D10, Komatsu PC800 y D275. Con su gama completa de herramientas, la prensa de pasadores MPP150 puede dar servicio a cadenas de oruga con diámetros de pasadores que van desde 22,0 mm (0,87") hasta 69,8 mm (2,75").



MPP150

La prensa MPP150 está disponible sin bomba hidráulica, o ofrecemos varias bombas resistentes que se adaptan a la potencia de un taller o camión de servicio. Para mayor seguridad durante el uso, también ofrecemos un manómetro opcional, una eslinga de elevación (diseñada específicamente para esta prensa) y una manta de seguridad (para protegerla de posibles residuos proyectados).

Para proteger su inversión y mantener todo organizado en un lugar conveniente, WTC ofrece una caja de almacenamiento/transporte personalizada o una plataforma de transporte con cubierta opcional para el almacenamiento y transporte seguro de su prensa MPP150, bomba y herramientas.



Caja de viaje
MPP150-SB



Esquí de viaje
MPP150-TS

Para más información o solicitar presupuesto; online: www.wtcmachinery.com • email: sales@wtcmachinery.com
phone: 800-248-8405 (U.S.) • 262-567-3993 (Intl.)



SECCIÓN 2 – MPP150 Especificaciones de la Prensa Portátil

DIMENSIONES

Peso (Menos suministro de energía hidráulica) 800 lbs (364 kg) **Longitud**64 pulgadas (1,63 m)
Ancho 12 pulgadas (0,30 m) **Altura**18 pulgadas (0,46 m)

AMBIENTAL

Rango de temperatura de funcionamiento- -40 to 100 °F (-40 to 38 °C) (Consulte la página 5 para obtener recomendaciones de aceite hidráulico.)

Condiciones de almacenamiento- 0 to 150 °F (-18 to 65 °C) Humedad sin condensación

CAPACIDAD DE PRENSADO

150 Toneladas cortas (136 toneladas)

RECORRIDO DEL CILINDRO HIDRÁULICO

Recorrido – 16 pulgadas (406 mm)

Diámetro interior– 6.12 inches (155 mm)

DIMENSIONES DE LA GARGANTA

Ancho – 27 pulgadas (686 mm)

Profundidad – 10 pulgadas (254 mm)

MODELOS DE PISTAS

Caterpillar D10 & Abajo, Komatsu D275, PC800 & Abajo, & Todas las Pistas Comparables

FUENTES DE ENERGÍA HIDRÁULICA

Presión Máxima (todas las unidades).....10,000 p.s.i. (690 bar)

	Bomba de Mano	Aire Comprimido	115V 60 Hz Eléctrico	220V 50 Hz Eléctrico*
MPP150 Model	MPP150-H	MPP150-A	MPP150-E	MPP150-220CE
Capacidad del Embalse	1.8 gal (6,8 l)	5 gal (18,9 l)	5 gal (18,9 l)	5 gal (18,9 l)
Flujo @ 150 psi (10,3 bar)	137 in ³ /min (2,2 lpm)**	500 in ³ /min (8,2 lpm)	550 in ³ /min (9,0 lpm)	700 in ³ /min (11,5 lpm)
Flujo @ 10000 psi (690 bar)	5 in ³ /min (0,08 lpm)**	100 in ³ /min (1,6 lpm)	39 in ³ /min (0,6 lpm)	60 in ³ /min (1,0 lpm)
Fuerza	-	4 Hp (3,0 kW)	1.6 Hp (1,2 kW)	1-3/4 Hp (1,3 kW)
Fuente de Alimentación	-	62 SCFM @ 100 psi 1,8 m ³ /min @ 6,9 bar	18 A @ 115 V 60Hz	11 A @ 220 V 50 Hz
Ancho	30.98" (0,79m)	12.5" (0,30 m)	12.0" (0,30 m)	19.7" (0,50 m)
Longitud	12.2" (0,31m)	18" (0,46 m)	25.8" (0,66 m)	24.0" (0,61 m)
Altura	11.73" (0,3m)	16.4" (0,42 m)	20.0" (0,51 m)	18.3" (0,47 m)
Peso Seco	60 lb (32 kg)	88 lb (40 kg)	90 lb (41 kg)	109 lb (50 kg)

* - Disponible Tambien:5.0 Amps, 220V 60Hz, 1 Phase (MPP150-220DOM)


5.0 Amps, 220V 50Hz, 1 Phase Non-CE Mark (MPP150-220-50)

** - Flujo basado en 20 Golpes por minute.

ESPECIFICACIONES SUJETAS A CAMBIOS SIN PREVIO AVISO

IDENTIFICACIÓN DE LA PIEZA

MPP150 Pin Press - General Arrangement



LISTADO DE MODELOS

- MPP150*** MPP150 con cilindro, sin piezas hidráulicas (bomba, mangueras y accesorios).
– Base de bomba y mangueras hidráulicas suministradas por el cliente.
- MPP150-H*** MPP150 con Bomba de Manual
– Incluye 34-2999 Bomba de Manual
- MPP150-E MPP150 con 115 V Bomba Eléctrica
– Incluye 34-3102 Bomba Eléctrica 115V 60 Hz
- MPP150-220 MPP150 con 220V 50Hz Bomba Eléctrica (Fuera de Unión Europea Y Fuera de América del Norte)
– Incluye 34-3103 Bomba Eléctrica 220V 50 Hz
- MPP150-220DOM MPP150 con 220V 60Hz Bomba Eléctrica (Unión Europea)
– Incluye 34-3103 Bomba Eléctrica 230V 60 Hz
- MPP150-220-CE*** MPP150 con CE-Certified 220V 50Hz Bomba Eléctrica (Unión Europea)
– Incluye 34-2074 Bomba Eléctrica 220V 50 Hz CE-Marked
- MPP150-A MPP150 con Bomba de Aire Comprimido
– Incluye 34-3003MPP Bomba neumática

***Certificado**

SECTION 6 – MPP150 Portable Pin Press Tooling



WARNING!

The MPP150 Portable Pin Press generates high forces, which present a risk of crush damage and flying debris. Only trained personnel familiar with its operation should use the MPP150. Always make sure the MPP150 and tooling are aligned and centered with track components before pressing. Always wear eye protection when operating the MPP150. Always keep clear of moving parts when the MPP150 is in use.



CAUTION!

Track condition affects the disassembly force, and some track models may exceed the capacity of the MPP150. It is the operator's responsibility to determine whether the MPP150 is adequate for a particular track.

The Tool Chart (starting on page 13) show the correct tooling for most crawler track models. For track models not listed, the drawing (below) shows the size ranges for Forcing Pins, Pin Adapters and Backing Bushing. See www.WTCmachinery.com for updated tool charts

Disassembling large track models - those with high pressing forces and long pin lengths - require pairs of Pin Tools. Use the short "Starter" Pin Tool to make the initial push, and then switch to the long "Finishing" Pin Tool to complete pressing out the pin.

FP150 Backing Bushings			
Item	Part Number	Description	Pin Size Range
9	A3541-001	Extra Large Backing	2.125" to 2.875" (53,9 to 73mm)
10	A3541	Large Backing Bushing	1.75" to 2.5" (44,5 to 63,5mm)
11	A3540	Medium Backing Bushing	1.25" to 1.75" (31,8 to 44,5mm)
12	A3539	Small Backing Bushing	1.25" (31,8mm) and Smaller

Forcing Pins		
Item	Part No.	Description
1	A3536	Pin Tool - (0.87" to 1.25" (22 to 31,7 mm))
2	A3537	Pin Tool - (1.25" to 1.37" (31,7 to 34,9 mm))
3	B3635	Pin Tool - (1.37" to 1.87" (34,9 to 47,6 mm))
4	B3815	Pin Tool - (1.87" to 2.12" (47,6 to 53,8 mm))
5	B3608	Pin Tool (short) - (2.12" to 2.50" (53,8 to 63,5 mm))
6	B3607	Pin Tool (long) - (2.12" to 2.50" (53,8 to 63,5 mm))
7	B3631	Pin Tool (short) - (2.50" to 3.00" (63,5 to 76,2 mm))
8	B3632	Pin Tool (long) - (2.50" to 3.00" (63,5 to 76,2 mm))

Pin Adapters		
Item	Part Number	Min/Max Pin Dia.
13	50-007-009	0.63" to 0.84" (15,9 to 21,4 mm)
14	50-007-008	0.84" to 0.94" (21,4 to 23,8 mm)
15	50-007-007	0.94" to 1.09" (23,8 to 27,7 mm)
16	50-007-006	1.09" to 1.22" (27,7 to 30,9 mm)
17	50-007-005	1.22" to 1.34" (30,9 to 34,1 mm)
18	50-007-004	1.34" to 1.47" (34,1 to 37,3 mm)
19	50-007-010	1.47" to 1.60" (37,3 to 40,7 mm)
20	50-007-003	1.60" to 1.72" (40,7 to 43,6 mm)
21	50-007-002	1.72" to 1.97" (43,6 to 50,0 mm)
22	50-007-001	1.97" to 2.22" (50,0 to 56,3 mm)
23	50-021-1	2.00" to 2.25" (50 to 57 mm)
24	50-021-2	2.25" to 2.50" (57 to 63 mm)
25	50-021-3	2.50" to 2.75" (63 to 70 mm)

Misc. Adapter Group		
Item	Part Number	Description
26	*A3535	Small Pin Tool Holder
27	*50-008-002	Pin Adapter Holder
28	*B2866	Cylinder-Side Cam-Lock Adapter
29	*529-522	Pin Locking Bolt
30	*50-020	Large Track Pin Holder
31	*50-008-001	Pin Assembly Tool
32	Pin Ass'y Tool	See Tooling Chart
33	*B2867	Backing Bar-Side Cam-Lock

200281	0.86" to 1.17"
25498	1.17" to 1.30"
25499	1.30" to 1.42"
25500	1.42" to 1.55"
25547	1.55" to 1.67"
25548	1.67" to 1.80"
25551	1.80" to 1.98"
25501	1.98" to 2.25"
25553	More than 2.25"
Part No.	Pin Diameter

Optional Forcing Pins (Not Shown)

MPP150 Tooling

* Items Included With MPP150



W1222 LINDEN ROAD, IXONIA, WISCONSIN 53036 USA

Phone: 800-248-8405 or 262-567-3993 • Fax: 262-567-4307 www.wtcmachinery.com

MANUFACTURERS/BENEFICIARY'S WARRANTY CERTIFICATE WTC MACHINERY, LLC WARRANTY

WTC MACHINERY, LLC warrants its products to be free from defects in material and workmanship under normal use and service for a period of twelve (12) months after date of shipment. WTC MACHINERY, LLC undertakes to be responsible for any defect that may arise due to faulty raw materials, design, workmanship and defective parts and to replace them without extra cost. Freight charges are the customer's responsibility. Our warranty is not transferable.

WTC MACHINERY, LLC shall have the option of requiring the return of all parts claimed defective. Parts proved to be defective, due to defect in workmanship and/or material, shall be either repaired or replaced free of charge, F.O.B. our designated factory. All parts warranty claims are subject to inspection by WTC MACHINERY, LLC and acceptance at the factory

Our warranty does not obligate us to bear the cost of labor or transportation charges in connection with the replacement or repair of defective parts and the removal and/or remounting of the parts repaired or replaced under this warranty, unless specifically authorized in writing by WTC MACHINERY, LLC. All parts returned to the factory must be shipped freight prepaid; no collect freight will be accepted by the factory. Forms authorizing such returns for inspection must accompany all returns.

This warranty shall not apply to products not manufactured by WTC MACHINERY, LLC.

Outside purchased equipment and accessories (not of WTC manufacture) are warranted only to the extent of the original equipment manufacturer's warranty and subject to their allowance to WTC MACHINERY, LLC. In this respect, our warranty obligations must conform and be limited to the warranty extended to WTC MACHINERY, LLC by its suppliers as extended to the customer.


We shall, in no event, be liable for consequential damages or contingent liability arising out of the failure of any unit or part to operate properly, or that is subject to:

- Ordinary operating wear, abuse, misuse, or overloading;
- Repairs or alterations by parties other than WTC MACHINERY, LLC;
- The use of improper fluids, contaminated fluids or improper filtering;
- The use of improper voltage hookup in the electrical connections of any equipment;
- Negligence, accident or damages due to deterioration during periods of storage by the purchaser prior to installation and operation;
- Damages occurred in shipment after leaving factory en route to customers' delivery point, as title to equipment passes to customer when loaded onboard for shipment, f.o.b. factory, and customer must place his own claim against damaged goods directly to the shipping company and not against WTC MACHINERY, LLC, its factory, or any of its personnel.
- Damages due to circumstances beyond the control of WTC MACHINERY, LLC and in connection with fulfilling any obligation under this warranty.

To the maximum extent permitted by applicable law, in no event shall WTC Machinery, LLC be liable for indirect, special, incidental or consequential damages resulting from personal injury, loss of business profits or business interruption from the use of its products, or from the inability to use its products.

This warranty is exclusive and is in lieu of all other expressed and implied warranties, including but not limited to implied warranties or merchantability and fitness for a particular purpose. WTC MACHINERY, LLC shall not be subject to any other obligations or liabilities whatsoever with respect to equipment manufactured or supplied by WTC MACHINERY, LLC, or services rendered to it.






CYLINDER-SIDE ADAPTERS
ALL MODELS




TRACK	CATERPILLAR PPR EXTRUDER TOOL	BERCO BPR2 EXTRUDER TOOL
D8N/R/T	M910-010	M910-010B
D9N/R/T	M910-1	M910-1B
D10 /N/R/T	M910-2*	M910-2B*
D11N/R/T	M910-3**	M910-3B**

Note: Extruder Tools Sold Individually - 2 Required


- * - Exceeds FP100 Capacity
** - Exceeds FP100, FP150 and MPP150 Capacity



BACK-SIDE ADAPTERS
FP100, FP150, MPP150



BACK-SIDE ADAPTERS
FP250, MPP250



WTC Machinery, LLC

W1222 LINDEN ROAD
IXONIA, WISCONSIN 53036 USA

TOLERANCES UNLESS
OTHERWISE SPECIFIED

FABRICATED DIMENSIONS +/- 1/16
FRACTIONAL DIMENSIONS +/- 1/64
DECIMAL DIMENSIONS +/- .010
INSIDE RADII 1/32
ANGULAR DIMENSIONS +/- 1/2
SURFACE FINISH 125

THIS DRAWING IS THE PROPERTY OF
WTC MACHINERY LLC
DO NOT USE, DISTRIBUTE OR COPY
WITHOUT EXPRESS PERMISSION

BREAK ALL SHARP EDGES
DO NOT SCALE DRAWING

NEXT ASSEMBLY

FP / MPP Portable Pin Presses

USED ON

Caterpillar PPR Track Chains

TITLE

**Caterpillar PPR Tracks
Pin Press Extruder Tools and Adapters**

SHEET

DATE

22.05.10

SIZE

DRAWING NUMBER

REV

DRAWN

WGT


N/A

B

FP/MPP-ETA

A


CYLINDER-SIDE ADAPTERS - ALL MODELS




Note: Wedge Ring Tools Sold in Sets
Each set includes -
- one Large End Tool (Rubber Plug end)
- one Small End Tool (Plastic Plug end)

* Exceeds Capacity of FP100



** Exceeds Capacity of FP100, FP150 and MPP150



BACK-SIDE ADAPTERS - FP100, FP150, MPP150



BACK-SIDE ADAPTERS - FP250, MPP250



WTC Machinery, LLC
W1222 LINDEN ROAD
IXONIA, WISCONSIN 53036 USA

TOLERANCES UNLESS OTHERWISE SPECIFIED

FABRICATED DIMENSIONS +/- 1/16
FRACTIONAL DIMENSIONS +/- 1/64
DECIMAL DIMENSIONS +/- .010
INSIDE RADII 1/32
ANGULAR DIMENSIONS +/- 1/2
SURFACE FINISH 125

THIS DRAWING IS THE PROPERTY OF WTC MACHINERY LLC
DO NOT USE, DISTRIBUTE OR COPY WITHOUT EXPRESS PERMISSION

BREAK ALL SHARP EDGES
DO NOT SCALE DRAWING

NEXT ASSEMBLY

FP / MPP Portable Pin Presses

USED ON

Komatsu Wedge Ring Track Chains

TITLE

**Komatsu Wedge Ring Tracks
Pin Press Wedge Ring Tools and Adapters**

SHEET

DATE

22.05.10

SIZE

B

DRAWING NUMBER

FP/MPP-WRTA

REV

A



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
AMER.AUGER	THT275	TRENCHER CHAIN		1.496	8.760	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915067
CASE	350		FLUSH	0.993	5.220	5.875	A3536	A3539	27	200281	50-008-002	50-007-007	27	915068
CASE	400		FLUSH	0.993	5.220	5.875	A3536	A3539	27	200281	50-008-002	50-007-007	27	915068
CASE	420		FLUSH	0.993	5.220	5.875	A3536	A3539	27	200281	50-008-002	50-007-007	27	915068
CASE	450		SALT	1.063	5.375	5.875	A3536	A3539	27	200281	50-008-002	50-007-007	27	915225
CASE	450		FLUSH	1.187	5.380	5.750	A3536	A3539	27	25498	50-008-002	50-007-006	27	915066
CASE	500		FLUSH	0.993	5.220	5.875	A3536	A3539	27	200281	50-008-002	50-007-007	27	915068
CASE	550	JAK0013968 & DN	SEALED	1.129	6.457	5.998	A3536	A3539	27	200281	50-008-002	50-007-006	27	915066
CASE	550		SEALED	1.129	6.575	6.290	A3536	A3539	27	200281	50-008-002	50-007-006	27	915144
CASE	550		SALT	1.129	6.575	6.290	A3536	A3539	27	200281	50-008-002	50-007-006	27	915144
CASE	560		FLUSH	0.993	5.220	5.875	A3536	A3539	27	200281	50-008-002	50-007-007	27	915068
CASE	600		SALT	1.063	5.375	5.875	A3536	A3539	27	200281	50-008-002	50-007-007	27	915225
CASE	650		SEALED	1.318	7.224	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CASE	650		SALT	1.318	7.224	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915158
CASE	700	S/N 7070351 & DN	RECESSED	1.248	6.500	6.250	A3536	A3539	27	25498	50-008-002	50-007-005	27	915056
CASE	750		RECESSED	1.375	6.940	6.250	B3635	A3540	27	25499	50-008-002	50-007-004	27	915069
CASE	800		RECESSED	1.248	6.500	6.250	A3536	A3539	27	25498	50-008-002	50-007-005	27	915056
CASE	850		SEALED	1.375	6.940	6.250	B3635	A3540	27	25499	50-008-002	50-007-004	27	915009
CASE	1000		RECESSED	1.248	6.500	6.250	A3536	A3539	27	25498	50-008-002	50-007-005	27	915056
CASE	1000	HD	RECESSED	1.375	6.940	6.250	B3635	A3540	27	25499	50-008-002	50-007-004	27	915069
CASE	1000		SEALED	1.375	6.940	6.250	B3635	A3540	27	25499	50-008-002	50-007-004	27	915009
CASE	1150		RECESSED	1.375	6.940	6.250	B3635	A3540	27	25499	50-008-002	50-007-004	27	915069
CASE	1150		SEALED	1.375	6.940	6.250	B3635	A3540	27	25499	50-008-002	50-007-004	27	915011
CASE	1450		SEALED	1.752	9.075	8.020	B3635	A3540	27	25548	50-008-002	50-007-002	27	915070
CASE	1550		SEALED	1.753	9.060	8.020	B3635	A3540	27	25548	50-008-002	50-007-002	27	915226
CASE	1550		SALT	1.753	9.060	8.020	B3635	A3540	27	25548	50-008-002	50-007-002	27	915006
CASE	1150B		SEALED	1.500	8.100	6.678	B3635	A3540	27	25500	50-008-002	50-007-010	27	915067
CASE	1150D	7310051 & PRIOR	SEALED	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CASE	1150D	7310051 & PRIOR	SALT	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CASE	1150E		SEALED	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CASE	1150E		SALT	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CASE	1155D	7311001 & PRIOR	SEALED	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CASE	1155D	7311001 & PRIOR	SALT	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CASE	1155E		SALT	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CASE	1155E		SEALED	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CASE	1450B		SEALED	1.752	9.075	8.020	B3635	A3540	27	25548	50-008-002	50-007-002	27	915070
CASE	1450B	S/N 8383001 & UP	SEALED	1.753	9.060	8.020	B3635	A3540	27	25548	50-008-002	50-007-002	27	915226
CASE	1450B		SALT	1.753	9.060	8.020	B3635	A3540	27	25548	50-008-002	50-007-002	27	915006
CASE	1455B		SEALED	1.752	9.075	8.020	B3635	A3540	27	25548	50-008-002	50-007-002	27	915070
CASE	1455B	S/N 8480001 & UP	SEALED	1.753	9.060	8.020	B3635	A3540	27	25548	50-008-002	50-007-002	27	915226
CASE	1455B		SALT	1.753	9.060	8.020	B3635	A3540	27	25548	50-008-002	50-007-002	27	915006
CASE	310G		FLUSH	0.994	5.219	5.875	A3536	A3539	27	200281	50-008-002	50-007-007	27	915068
CASE	350B		SEALED	0.994	5.219	5.875	A3536	A3539	27	200281	50-008-002	50-007-007	27	915224
CASE	450A	S/N 3030801 & UP	SEALED	1.250	6.540	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915069
CASE	450B		SEALED	1.250	6.540	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915069

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
CASE	450C		SEALED	1.129	6.457	5.998	A3536	A3539	27	200281	50-008-002	50-007-006	27	915066
CASE	450C		SALT	1.129	6.460	6.000	A3536	A3539	27	200281	50-008-002	50-007-006	27	915046
CASE	455C		SALT	1.129	6.460	6.000	A3536	A3539	27	200281	50-008-002	50-007-006	27	915046
CASE	550E		SEALED	1.129	6.575	6.290	A3536	A3539	27	200281	50-008-002	50-007-006	27	915144
CASE	550E		SALT	1.129	6.575	6.290	A3536	A3539	27	200281	50-008-002	50-007-006	27	915144
CASE	550G	Floating Bushing	SEALED	1.129	6.575	6.290	A3536	A3539	27	200281	50-008-002	50-007-006	27	915144
CASE	850B		SEALED	1.375	6.940	6.250	B3635	A3540	27	25499	50-008-002	50-007-004	27	915009
CASE	850D		SALT	1.318	7.220	6.250	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CASE	850D		SEALED	1.318	7.224	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CASE	850D		SALT	1.318	7.224	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915158
CASE	850D		SEALED	1.375	6.940	6.250	B3635	A3540	27	25499	50-008-002	50-007-004	27	915011
CASE	850E	AFTER 4-1-89	SEALED	1.318	7.224	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CASE	850E	AFTER 4-1-89	SALT	1.318	7.224	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915158
CASE	850G		SEALED	1.318	7.224	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CASE	850G		SALT	1.318	7.224	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915158
CASE	850H		SEALED	1.318	7.224	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CASE	850H		SALT	1.318	7.224	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915158
CASE	850K		SEALED	1.318	7.224	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CASE	850K		SALT	1.318	7.224	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915158
CASE	855D		SALT	1.318	7.220	6.250	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CASE	855D	AFTER 4-1-89	SEALED	1.318	7.224	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CASE	855D	AFTER 4-1-89	SALT	1.318	7.224	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915158
CASE	855D		SEALED	1.375	6.940	6.250	B3635	A3540	27	25499	50-008-002	50-007-004	27	915011
CAT	30		RECESS	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CAT	215	w/ 5/8 BOLT	SEALED	1.314	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CAT	215	w/ 9/16 BOLT	SEALED	1.315	6.370	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
CAT	219		SEALED	1.442	8.120	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	225		SEALED	1.252	9.060	7.984	A3537	A3539	30	25498	50-008-002	50-007-005	27	915003
CAT	225	EXC	SEALED	1.314	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CAT	225		SEALED	1.752	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	227		SEALED	1.252	9.060	7.984	A3537	A3539	30	25498	50-008-002	50-007-005	27	915003
CAT	227		SEALED	1.752	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	229		SEALED	1.252	9.060	7.984	A3537	A3539	30	25498	50-008-002	50-007-005	27	915003
CAT	229		SEALED	1.752	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	235	EXC	SEALED	1.252	9.060	7.984	A3537	A3539	30	25498	50-008-002	50-007-005	27	915003
CAT	235	EXC	SEALED	1.752	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	235		SEALED	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
CAT	245	Berco	SEALED	2.004	11.437	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	
CAT	245	EXC	SEALED	2.253	11.259	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	32	915005
CAT	308	Mini EXC	GREASE	0.945	5.157	6.100	A3536	A3539	27	200281	50-008-002	50-007-007	27	915281
CAT	311	EXC	SEALED	1.321	7.010	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915059
CAT	312	EXC	SEALED	1.321	7.010	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915059
CAT	315	EXC	SEALED	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915140
CAT	317	EXC	SEALED	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915140
CAT	320	EXC	SEALED	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915140

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
CAT	322	EXC	SEALED	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915140
CAT	325	EXC	SEALED	1.654	9.055	8.000	B3635	A3540	27	25547	50-008-002	50-007-003	27	915141
CAT	329	EXC	GREASE	1.650	9.000	8.000	B3635	A3540	27	25547	50-008-002	50-007-003	27	915275
CAT	330	EXC	SEALED	1.811	9.665	8.500	B3635	A3541	27	25551	50-008-002	50-007-002	30	915015
CAT	336	EXC	SEALED	1.750	9.625	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915020
CAT	345	EXC	SEALED	2.003	11.438	8.500	B3815	A3541	30	25551	50-008-002	50-007-001	32	915142
CAT	350		SEALED	2.003	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915001
CAT	365	EXC	SEALED	2.253	12.244	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915139
CAT	375	EXC	SEALED	2.253	12.244	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915139
CAT	390	EXC	SEALED	2.165	12.402	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915284
CAT	561	PIPELAYER	SEALED	1.442	8.125	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	571		SEALED	1.752	9.875	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
CAT	572		SEALED	1.752	9.875	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
CAT	572		SEALED	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
CAT	578		PPR	1.878	9.650	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915207
CAT	578	PIPELAYER	SALT	1.880	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	583		SEALED	1.752	11.438	7.985	B3635	A3540	30	25548	50-008-002	50-007-002	32	915013
CAT	589		PPR	2.000	10.770	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	30	915064
CAT	589	PIPELAYER	SALT	2.000	11.437	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915093
CAT	594		SEALED	2.252	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915005
CAT	931		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	931		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	933		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	933		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	939		SALT	1.318	7.535	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915149
CAT	941	w/ 9/16 BOLT	SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
CAT	941	w/ 5/8 BOLT	SEALED	1.314	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CAT	941		SALT	1.314	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915052
CAT	943	HI RAIL	SALT	1.314	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915052
CAT	943	HI RAIL	SALT	1.315	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
CAT	951		SALT	1.442	8.120	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	951		SEALED	1.442	8.125	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	953	HYBRID	SALT	1.442	8.100	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915278
CAT	953		SALT	1.442	8.120	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	953	HI RAIL	SALT	1.442	8.120	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	953	LGP	SALT	1.442	8.120	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	955		SEALED	1.252	9.060	7.984	A3537	A3539	30	25498	50-008-002	50-007-005	27	915003
CAT	955	HD	SEALED	1.442	8.125	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	955		SEALED	1.752	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	955		SALT	1.753	9.060	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	963		SALT	1.753	9.060	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	963	HI RAIL	SALT	1.753	9.060	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	963	Berco	SALT	1.753	9.060	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	973		SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	973	HI RAIL	SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006

Note: Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
CAT	973	LGP	SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	973		SEALED	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
CAT	973	HI RAIL	SALT	1.878	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915201
CAT	977		SEALED	1.442	8.125	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	977	OPT FORMER	SEALED	1.442	8.125	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	977		SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	977		SEALED	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
CAT	983		SALT	2.002	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915007
CAT	983		SEALED	2.003	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915001
CAT	5080		SEALED	2.253	12.244	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915139
CAT	14A		SEALED	1.752	11.438	7.985	B3635	A3540	30	25548	50-008-002	50-007-002	32	915013
CAT	17A		SEALED	1.752	9.875	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
CAT	215A		SEALED	1.442	8.120	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	225B	EXC	SEALED	1.442	8.120	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	225C	EXC	SEALED	1.442	8.120	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	231D		SEALED	1.252	9.060	7.984	A3537	A3539	30	25498	50-008-002	50-007-005	27	915003
CAT	231D		SEALED	1.752	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	235-6	EXC	SEALED	1.750	9.062	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915237
CAT	235D		SEALED	2.003	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915001
CAT	245S		SEALED	2.003	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915001
CAT	299D	Berco BC2428	SALT	1.036	5.795	5.510	A3536	A3539	27	200281	50-008-002	50-007-007	27	915044
CAT	307C		GREASE	0.940	5.150	6.060	A3536	A3539	27	200281	50-008-002	50-007-007	27	915169
CAT	312C	EXC	GREASE	1.320	7.000	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915059
CAT	313B	EXC	SEALED	1.321	7.010	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915059
CAT	314B	EXC	SEALED	1.321	7.010	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915059
CAT	315B	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915236
CAT	315C	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915170
CAT	315L	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915003
CAT	318C	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915170
CAT	320B	EXC	SEALED	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915140
CAT	320C	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915170
CAT	320D	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915170
CAT	320EL	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915170
CAT	320L	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915170
CAT	322B	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915236
CAT	322C	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915170
CAT	324D	EXC	GREASE	1.442	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915170
CAT	325BL	EXC	SEALED	1.654	9.055	8.000	B3635	A3540	27	25547	50-008-002	50-007-003	27	915141
CAT	325C	EXC	GREASE	1.650	9.050	7.985	B3635	A3540	27	25547	50-008-002	50-007-003	27	915141
CAT	330B	EXC	SEALED	1.811	9.665	8.500	B3635	A3541	27	25551	50-008-002	50-007-002	30	915015
CAT	330B	EXC	GREASE	1.811	9.665	8.500	B3635	A3541	27	25551	50-008-002	50-007-002	30	915185
CAT	330C	EXC	SEALED	1.811	9.665	8.500	B3635	A3541	27	25551	50-008-002	50-007-002	30	915015
CAT	336EL	EXC	GREASE	1.811	9.665	8.500	B3635	A3541	27	25551	50-008-002	50-007-002	30	915015
CAT	336NGH	EXC	SEALED	1.807	8.246	8.500	B3635	A3540	27	25551	50-008-002	50-007-002	27	915336
CAT	345B		SEALED	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012

Note: Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
CAT	345B	EXC	SALT	1.877	9.882	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915200
CAT	345BL	EXC	SALT	1.877	9.882	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915200
CAT	345CL		GREASE	1.811	9.843	7.850	B3635	A3541	27	25551	50-008-002	50-007-002	30	915263
CAT	349E		SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915055
CAT	349F	EXC	PPR2	1.877	9.805	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915017
CAT	365BL	EXC	SEALED	2.253	12.244	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915139
CAT	385B	EXC	SEALED	2.253	13.188	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915168
CAT	561H		SALT	1.318	7.535	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915149
CAT	561H	HD	SALT	1.418	8.445	6.735	B3635	A3540	27	25499	50-008-002	50-007-004	27	915145
CAT	571A		SEALED	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
CAT	571A		SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	583R	PIPELAYER	SALT	1.880	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	935B		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	935B		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	935C		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	951B		SEALED	1.442	8.125	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	951B		SEALED	1.442	8.125	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	951C		SEALED	1.442	8.125	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	953C		SALT	1.442	8.120	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915242
CAT	953K	Conventional Track	SALT	1.442	8.120	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915242
CAT	955K		SEALED	1.442	8.125	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	977K		SEALED	1.752	9.875	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
CAT	AP1050		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	D2		RECESS	1.127	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	916040
CAT	D2		SEALED	1.125	6.180	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915040
CAT	D3		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	D3		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	D3B		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	D3B		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	D3C		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	D3G		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	D3G		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	D3K		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	D4		RECESS	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CAT	D4		SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
CAT	D4	Berco	UNSEALED	1.319	7.224	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915050
CAT	D4	w/ 1/2 BOLT	SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915137
CAT	D4	w/ 9/16 BOLT	SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915137
CAT	D4		SALT	1.314	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915052
CAT	D4B		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	D4B		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	D4C		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	D4C		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	D4C	w/ 1/2 BOLT	SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915137
CAT	D4C	w/ 9/16 BOLT	SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915137

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
CAT	D4D		SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
CAT	D4D		SEALED	1.314	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CAT	D4D		SALT	1.314	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915052
CAT	D4D	w/ 1/2 BOLT	SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915137
CAT	D4D	w/ 9/16 BOLT	SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915137
CAT	D4E		SALT	1.314	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915052
CAT	D4G		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	D4G		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	D4H		SALT	1.315	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915124
CAT	D4H	LGP	PPR	1.315	7.287	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915247
CAT	D4H		SALT	1.318	7.535	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915149
CAT	D4H	TSK CUS SKD	SALT	1.318	7.535	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915149
CAT	D4H	HD	SALT	1.418	8.445	6.735	B3635	A3540	27	25499	50-008-002	50-007-004	27	915145
CAT	D4K		SALT	1.126	6.161	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915082
CAT	D4K2		SALT	1.130	6.144	6.250	A3536	A3539	27	200281	50-008-002	50-007-006	27	915065
CAT	D5		SALT	1.442	8.120	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	D5	PRO	SALT	1.442	8.120	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	D5		SEALED	1.442	8.125	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	D5B		SALT	1.442	8.120	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	D5B		SEALED	1.442	8.125	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	D5C		SALT	1.318	7.535	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915149
CAT	D5G		SALT	1.318	7.535	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915149
CAT	D5G	XL	SALT	1.318	7.535	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915149
CAT	D5H		SALT	1.443	8.122	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	D5H	TSK CUS SKD	SALT	1.443	8.183	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
CAT	D5H	HD	SALT	1.495	9.392	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915145
CAT	D5K		SALT	1.318	7.535	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915149
CAT	D5M		SALT	1.418	8.445	6.735	B3635	A3540	27	25499	50-008-002	50-007-004	27	915145
CAT	D5N		SALT	1.418	8.445	6.735	B3635	A3540	27	25499	50-008-002	50-007-004	27	915145
CAT	D6		RECESS	1.442	8.125	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915014
CAT	D6		SEALED	1.442	8.125	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	D6		SALT	1.752	9.060	7.985	B3635	A3540	27	25548	50-008-002	50-007-002	27	915205
CAT	D6		SALT	1.753	9.060	7.985	B3635	A3540	27	25548	50-008-002	50-007-002	27	915081
CAT	D6 / XE	HDXL	PPR2	1.732	9.882	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915326
CAT	D6B		SEALED	1.442	8.125	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
CAT	D6C		SEALED	1.252	9.060	7.984	A3537	A3539	30	25498	50-008-002	50-007-005	27	915003
CAT	D6C		SEALED	1.752	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	D6C		SALT	1.753	9.060	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	D6D		SEALED	1.252	9.060	7.984	A3537	A3539	30	25498	50-008-002	50-007-005	27	915003
CAT	D6D		SEALED	1.752	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	D6D		SALT	1.753	9.060	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	D6E		SALT	1.753	9.060	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	D6H	LGP	SALT	1.753	9.060	7.985	B3635	A3540	27	25548	50-008-002	50-007-002	27	915081
CAT	D6H		SALT	1.753	9.060	7.985	B3635	A3540	27	25548	50-008-002	50-007-002	27	915081
CAT	D6H	LGP	PPR	1.753	9.150	7.985	B3635	A3540	27	25548	50-008-002	50-007-002	27	915143

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
CAT	D6H	HD	SALT	1.753	10.315	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	30	915143
CAT	D6K2		SALT	1.495	9.392	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915145
CAT	D6M		SALT	1.495	9.392	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915145
CAT	D6M	PPR2	SALT	1.496	8.946	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915335
CAT	D6N		SALT	1.495	9.392	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915145
CAT	D6N	PPR2	SALT	1.496	8.946	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915335
CAT	D6R		SALT	1.753	10.315	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	30	915143
CAT	D6T		SALT	1.753	10.315	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	30	915143
CAT	D6T	PPR2	SALT	1.753	10.315	7.984	B3635	A3540	30	25548	50-008-002	50-007-002	30	915337
CAT	D6	ITR UL202C3F00	SALT	1.754	9.063	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915344
CAT	D7		RECESS	1.752	9.875	7.985	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
CAT	D7		SEALED	1.752	9.875	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
CAT	D7	Berco	SEALED	1.756	9.902	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	30	
CAT	D7		SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	D7C		SEALED	1.752	9.875	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
CAT	D7D		RECESS	1.752	9.875	7.985	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
CAT	D7D		SEALED	1.752	9.875	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
CAT	D7E	1970's Non Electric	SEALED	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
CAT	D7E	1970's Non Electric	SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	D7E	Electric Drive	SALT	1.878	10.885	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915150
CAT	D7E / H / R	HDXL	PPR2	1.879	10.420	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915327
CAT	D7F		SEALED	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
CAT	D7F		SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	D7G		SEALED	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
CAT	D7G		SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	D7G	LGP	SALT	1.877	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	D7H	LGP	PPR	1.878	9.925	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915007
CAT	D7H		SALT	1.878	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915103
CAT	D7H	HD	SALT	1.878	10.875	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915150
CAT	D7R		SALT	1.878	10.875	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915150
CAT	D8		RECESS	1.752	11.438	7.948	B3635	A3540	30	25548	50-008-002	50-007-002	32	915206
CAT	D8		SEALED	1.752	11.438	7.985	B3635	A3540	30	25548	50-008-002	50-007-002	32	915013
CAT	D8	TREK TRACK	SALT	1.880	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	D8		SALT	2.002	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915007
CAT	D8 HD XL	Links 502-6149 / 6150		1.878	9.650	8.592	B3815	A3541	30	25551	50-008-002	50-007-002	30	915207
CAT	D8D		SEALED	1.752	11.438	7.985	B3635	A3540	30	25548	50-008-002	50-007-002	32	915013
CAT	D8E		SEALED	1.752	11.438	7.985	B3635	A3540	30	25548	50-008-002	50-007-002	32	915013
CAT	D8F		SEALED	1.752	11.438	7.985	B3635	A3540	30	25548	50-008-002	50-007-002	32	915013
CAT	D8G		SEALED	1.752	11.438	7.985	B3635	A3540	30	25548	50-008-002	50-007-002	32	915013
CAT	D8H		SALT	2.002	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915007
CAT	D8H		SEALED	2.003	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915001
CAT	D8H	ITM		2.004	11.500	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	
CAT	D8K		SALT	2.002	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915007
CAT	D8K		SEALED	2.003	11.438	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915001
CAT	D8L		SALT	1.880	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
CAT	D8N		PPR	1.878	9.650	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915207
CAT	D8N		SALT	1.880	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	D8R		PPR	1.878	9.650	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915207
CAT	D8R		SALT	1.880	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	D8T		PPR	1.878	9.650	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915207
CAT	D8T		SALT	1.880	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
CAT	D8XL			1.878	9.650	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915207
CAT	D9		SEALED	2.002	12.000	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	35	915208
CAT	D9		SALT	2.252	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915008
CAT	D9D		SEALED	2.252	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915005
CAT	D9E		SEALED	2.252	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915005
CAT	D9G		SEALED	2.252	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915005
CAT	D9G		SALT	2.252	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915008
CAT	D9H		SEALED	2.252	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915005
CAT	D9H		SALT	2.252	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915008
CAT	D9L		PPR	2.000	10.770	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	30	915064
CAT	D9L		SALT	2.000	11.437	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915093
CAT	D9N		PPR	2.000	10.440	9.449	B3815	A3541	30	25551	50-008-002	50-007-001	30	915253
CAT	D9N		SALT	2.003	10.980	9.450	B3815	A3541	30	25551	50-008-002	50-007-001	30	915092
CAT	D9R		PPR	2.000	10.440	9.449	B3815	A3541	30	25551	50-008-002	50-007-001	30	915253
CAT	D9R		SALT	2.003	10.980	9.450	B3815	A3541	30	25551	50-008-002	50-007-001	30	915092
CAT	D9T		PPR	2.000	10.440	9.449	B3815	A3541	30	25551	50-008-002	50-007-001	30	915253
CAT	D9T	Berco BPR2 (CR7611)	SALT	2.000	11.260	9.449	B3815	A3541	30	25551	50-008-002	50-007-001	32	915253
CAT	D9T		SALT	2.003	10.980	9.450	B3815	A3541	30	25551	50-008-002	50-007-001	30	915092
CAT	D10		PPR	2.252	11.974	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915240
CAT	D10		SALT	2.253	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915063
CAT	D10N		PPR	2.253	11.970	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915246
CAT	D10N	ITM	PPR	2.250	11.968	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915351
CAT	D10N		SALT	2.253	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915104
CAT	D10R		PPR	2.253	11.970	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915246
CAT	D10R		SALT	2.253	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915104
CAT	D10T		SALT	2.253	12.250	10.250	B3607/8	A3541	35	25501	50-020	50-021-2	35	915104
CAT	D11		SALT	2.626	13.810	12.500	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915202
CAT	D11N		PPR	2.626	13.812	12.500	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915203
CAT	D11R	ITR Snap Ring	IPR	2.626	13.812	12.500	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915203ITM
CAT	D11R		PPR	2.626	13.812	12.500	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915203
CAT	D11T		PPR	2.626	13.812	12.500	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915203
CAT	E110B		SEALED	1.319	7.008	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915059
CAT	E120B		SEALED	1.319	7.008	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915059
CAT	E180		SEALED	1.439	8.126	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915128
CAT	E200B		SEALED	1.445	8.150	7.500	B3635	A3540	27	25500	50-008-002	50-007-004	27	915133
CAT	E240		SEALED	1.445	8.150	7.500	B3635	A3540	27	25500	50-008-002	50-007-004	27	915133
CAT	E300B		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
CAT	E450		UNSEALED	1.873	10.000	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915038
CAT	E70		SEALED	0.945	5.512	5.315	A3536	A3539	27	200281	50-008-002	50-007-007	27	915129

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
CAT	E70B		SEALED	0.945	5.512	5.315	A3536	A3539	27	200281	50-008-002	50-007-007	27	915129
CAT	EL180		SEALED	1.439	8.126	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915128
CAT	EL200B		SEALED	1.445	8.150	7.500	B3635	A3540	27	25500	50-008-002	50-007-004	27	915133
CAT	EL240		SEALED	1.445	8.150	7.500	B3635	A3540	27	25500	50-008-002	50-007-004	27	915133
CAT	EL300A		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
CAT	EL300B		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
CAT	EL300B		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915038
CAT	FB227		SEALED	1.252	9.060	7.984	A3537	A3539	30	25498	50-008-002	50-007-005	27	915003
CAT	FB227		SEALED	1.752	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
CAT	MHI 180-8		SEALED	1.439	8.126	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915128
CAT	MHI 180-8LC		SEALED	1.439	8.126	6.906	B3635	A3540	27	25500	50-008-002	50-007-004	27	915128
CAT	MHI 300LC-8		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
CAT	PR450		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	R2-15-22		RECESS	1.127	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	916040
CAT	R4		RECESS	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915011
CAT	SF350		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
CAT	TR225		SEALED	1.129	6.156	6.125	A3536	A3539	27	200281	50-008-002	50-007-006	27	915004
DRESSER	150		SEALED	1.375	6.690	6.490	B3635	A3540	27	25499	50-008-002	50-007-004	27	915048
DRESSER	175		SEALED	1.625	7.870	6.992	B3635	A3540	27	25547	50-008-002	50-007-003	27	915041
DRESSER	500		RECESSED	1.125	5.360	6.000	A3536	A3539	27	200281	50-008-002	50-007-006	27	915044
DRESSER	100B		SEALED	1.250	5.970	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915034
DRESSER	100C		SEALED	1.250	6.500	5.998	A3537	A3539	27	25498	50-008-002	50-007-005	27	915040
DRESSER	100E		SEALED	1.250	6.500	5.990	A3537	A3539	27	25498	50-008-002	50-007-005	27	915100
DRESSER	100G		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	125C		SEALED	1.375	6.690	6.490	B3635	A3540	27	25499	50-008-002	50-007-004	27	915048
DRESSER	125E		SEALED	1.375	6.690	6.490	B3635	A3540	27	25499	50-008-002	50-007-004	27	915048
DRESSER	125G		UNSEALED	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915213
DRESSER	125G		SEALED	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915040
DRESSER	125G		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	175B		SEALED	1.625	7.870	6.992	B3635	A3540	27	25547	50-008-002	50-007-003	27	915041
DRESSER	175B		SEALED	1.750	8.810	7.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915036
DRESSER	175C		SEALED	1.750	8.810	7.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915036
DRESSER	250B		SEALED	1.750	9.310	7.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915036
DRESSER	250C		SEALED	1.750	9.310	7.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915036
DRESSER	500E		UNSEALED	1.125	5.300	5.990	A3536	A3539	27	200281	50-008-002	50-007-006	27	915209
DRESSER	D32		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	D32E		SEALED	1.250	6.500	5.998	A3537	A3539	27	25498	50-008-002	50-007-005	27	915040
DRESSER	D32E		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	D32P		SEALED	1.250	6.500	5.998	A3537	A3539	27	25498	50-008-002	50-007-005	27	915040
DRESSER	D32-P1		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	D38E		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	D38P-1		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	D39		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	D39E		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	D87E-2		SALT	1.874	10.430	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915077

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
DRESSER	D87P		SALT	1.874	10.430	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915077
DRESSER	T340		FLUSH	1.010	4.750	6.000	A3536	A3539	27	200281	50-008-002	50-007-007	27	915028
DRESSER	T5		FLUSH	1.010	4.750	6.000	A3536	A3539	27	200281	50-008-002	50-007-007	27	915028
DRESSER	T6		SEALED	1.250	5.970	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915034
DRESSER	T7		SEALED	1.250	6.500	5.998	A3537	A3539	27	25498	50-008-002	50-007-005	27	915040
DRESSER	TD12		SALT	1.500	8.030	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915095
DRESSER	TD12		SEALED	1.750	8.030	7.490	B3635	A3540	27	25548	50-008-002	50-007-002	27	915095
DRESSER	TD12A		UNSEALED	1.500	8.030	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915210
DRESSER	TD12B		UNSEALED	1.500	8.030	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915210
DRESSER	TD12C		UNSEALED	1.625	8.810	7.490	B3635	A3540	27	25547	50-008-002	50-007-003	27	915211
DRESSER	TD12C-XP		SEALED	1.629	8.820	7.490	B3635	A3540	27	25547	50-008-002	50-007-003	27	915083
DRESSER	TD14		SEALED	1.625	7.870	6.992	B3635	A3540	27	25547	50-008-002	50-007-003	27	915041
DRESSER	TD15		SEALED	1.625	7.870	6.992	B3635	A3540	27	25547	50-008-002	50-007-003	27	915041
DRESSER	TD15B		SEALED	1.625	7.870	6.992	B3635	A3540	27	25547	50-008-002	50-007-003	27	915041
DRESSER	TD15B		SEALED	1.750	8.810	7.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915036
DRESSER	TD15C		SALT	1.625	8.810	7.490	B3635	A3540	27	25547	50-008-002	50-007-003	27	915021
DRESSER	TD15C	LGP	SALT	1.625	8.810	7.490	B3635	A3540	27	25547	50-008-002	50-007-003	27	915021
DRESSER	TD15C	SPLIT	UNSEALED	1.625	8.810	7.490	B3635	A3540	27	25547	50-008-002	50-007-003	27	915211
DRESSER	TD15C	SPLIT	SEALED	1.625	8.810	7.490	B3635	A3540	27	25547	50-008-002	50-007-003	27	915021
DRESSER	TD15C		SEALED	1.750	8.810	7.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915036
DRESSER	TD15E		SEALED	1.750	8.810	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915108
DRESSER	TD15E		SALT	1.750	8.810	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915109
DRESSER	TD15E	LGP	SALT	1.750	8.810	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915109
DRESSER	TD20B		SEALED	1.750	9.310	7.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915036
DRESSER	TD20C		SEALED	1.750	9.310	7.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915036
DRESSER	TD20C		SEALED	1.875	9.310	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	27	915035
DRESSER	TD20E		UNSEALED	1.874	10.430	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915212
DRESSER	TD20E		SALT	1.874	10.430	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915077
DRESSER	TD20E	SPLIT	SEALED	1.875	10.430	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915077
DRESSER	TD20E		SEALED	1.875	10.440	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915038
DRESSER	TD20G		UNSEALED	1.874	10.430	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915212
DRESSER	TD20G		SALT	1.874	10.430	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915077
DRESSER	TD20G	LGP	SALT	1.874	10.430	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915077
DRESSER	TD24		SEALED	1.875	11.000	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915037
DRESSER	TD25B		SEALED	1.875	11.000	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915037
DRESSER	TD25C		SEALED	2.125	11.000	9.870	B3607/8	A3541	35	25501	50-008-002	50-007-001	30	915102
DRESSER	TD25C		SALT	2.125	11.000	9.870	B3607/8	A3541	35	25501	50-008-002	50-007-001	30	915102
DRESSER	TD25E		SEALED	2.125	11.000	9.870	B3607/8	A3541	35	25501	50-008-002	50-007-001	30	915102
DRESSER	TD25E		SALT	2.125	11.000	9.870	B3607/8	A3541	35	25501	50-008-002	50-007-001	30	915102
DRESSER	TD25E	SPLIT	SEALED	2.125	11.000	9.870	B3607/8	A3541	35	25501	50-008-002	50-007-001	30	915102
DRESSER	TD25G		UNSEALED	2.125	11.000	9.870	B3607/8	A3541	35	25501	50-008-002	50-007-001	30	915102
DRESSER	TD25G		SALT	2.125	11.000	9.870	B3607/8	A3541	35	25501	50-008-002	50-007-001	30	915102
DRESSER	TD30		SEALED	2.125	11.000	9.870	B3607/8	A3541	35	25501	50-008-002	50-007-001	30	915102
DRESSER	TD30		SALT	2.125	11.000	9.870	B3607/8	A3541	35	25501	50-008-002	50-007-001	30	915102
DRESSER	TD4		FLUSH	1.010	4.750	6.000	A3536	A3539	27	200281	50-008-002	50-007-007	27	915028

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
DRESSER	TD40	SPLIT	SALT	2.456	12.600	11.020	B3607/8	A3541	35	25553	50-020	50-021-2	35	915101
DRESSER	TD40	SPLIT	SEALED	2.456	12.600	11.020	B3607/8	A3541	35	25553	50-020	50-021-2	35	915101
DRESSER	TD5		FLUSH	1.010	4.750	6.000	A3536	A3539	27	200281	50-008-002	50-007-007	27	915028
DRESSER	TD6		SEALED	1.250	5.970	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915034
DRESSER	TD7		SEALED	1.250	6.500	5.998	A3537	A3539	27	25498	50-008-002	50-007-005	27	915040
DRESSER	TD7C		SEALED	1.250	6.500	5.998	A3537	A3539	27	25498	50-008-002	50-007-005	27	915040
DRESSER	TD7E		SEALED	1.250	6.500	5.990	A3537	A3539	27	25498	50-008-002	50-007-005	27	915100
DRESSER	TD7G		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	TD7H		UNSEALED	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915213
DRESSER	TD8C		SEALED	1.375	6.690	6.490	B3635	A3540	27	25499	50-008-002	50-007-004	27	915048
DRESSER	TD8E		SEALED	1.375	6.690	6.490	B3635	A3540	27	25499	50-008-002	50-007-004	27	915048
DRESSER	TD8G		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
DRESSER	TD8G		SEALED	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915040
DRESSER	TD-8G		UNSEALED	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915213
DRESSER	TD9B		SEALED	1.375	6.690	6.490	B3635	A3540	27	25499	50-008-002	50-007-004	27	915048
DRESSER	TD9H		SALT	1.312	6.690	6.490	A3537	A3540	27	25499	50-008-002	50-007-005	27	915133
FIAT	31		UNSEALED	2.374	12.953	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915142
FIAT	31		SALT	2.374	12.953	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915221
FIAT	652		UNSEALED	1.250	6.240	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915004
FIAT	653		UNSEALED	1.250	6.240	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915004
FIAT	655		UNSEALED	1.250	6.240	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915004
FIAT	12G		UNSEALED	1.874	10.270	7.858	B3815	A3541	30	25551	50-008-002	50-007-002	30	915020
FIAT	12G		SEALED	1.876	10.270	7.850	B3815	A3541	30	25551	50-008-002	50-007-002	30	915020
FIAT	12GB		SEALED	1.878	10.270	7.858	B3815	A3541	30	25551	50-008-002	50-007-002	30	915030
FIAT	14B		UNSEALED	1.578	8.661	7.480	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	41B		UNSEALED	2.622	14.000	11.281	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915218
FIAT	41B		SALT	2.622	14.000	11.281	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915218
FIAT	AD10		UNSEALED	1.459	7.874	6.929	B3635	A3540	27	25500	50-008-002	50-007-004	27	915022
FIAT	AD10B		UNSEALED	1.459	7.874	6.929	B3635	A3540	27	25500	50-008-002	50-007-004	27	915022
FIAT	AD12		SALT	1.577	8.660	6.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	AD12		UNSEALED	1.578	8.661	7.480	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	AD14		SALT	1.577	8.660	6.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	AD14		UNSEALED	1.578	8.661	7.480	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	AD18		UNSEALED	1.870	9.840	8.503	B3815	A3541	30	25551	50-008-002	50-007-002	30	915019
FIAT	AD20		UNSEALED	1.870	9.840	8.503	B3815	A3541	30	25551	50-008-002	50-007-002	30	915019
FIAT	AD4		UNSEALED	0.984	5.280	5.512	A3536	A3539	27	200281	50-008-002	50-007-007	27	915028
FIAT	AD5		UNSEALED	1.181	6.100	6.299	A3536	A3539	27	25498	50-008-002	50-007-006	27	915027
FIAT	AD6		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	AD7		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	AD7C		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	AD8		UNSEALED	1.380	7.126	6.693	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	AD9		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	B1		UNSEALED	0.984	5.280	5.512	A3536	A3539	27	200281	50-008-002	50-007-007	27	915028
FIAT	BD10		UNSEALED	1.459	7.874	6.929	B3635	A3540	27	25500	50-008-002	50-007-004	27	915022
FIAT	BD10B		UNSEALED	1.459	7.874	6.929	B3635	A3540	27	25500	50-008-002	50-007-004	27	915022

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
FIAT	BD12		SALT	1.577	8.660	6.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	BD12		UNSEALED	1.578	8.661	7.480	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	BD14		SALT	1.577	8.660	6.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	BD14		UNSEALED	1.578	8.661	7.480	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	BD18		UNSEALED	1.870	9.840	8.503	B3815	A3541	30	25551	50-008-002	50-007-002	30	915019
FIAT	BD20		UNSEALED	1.870	9.840	8.503	B3815	A3541	30	25551	50-008-002	50-007-002	30	915019
FIAT	BD7		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	BD7C		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	BD8		UNSEALED	1.380	7.126	6.693	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	BD9		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	F318		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	FA200		SALT	1.577	8.660	6.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	FD14		SALT	1.577	8.660	6.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	FD20		UNSEALED	1.873	9.843	8.504	B3815	A3541	30	25551	50-008-002	50-007-002	30	915019
FIAT	FD20		SALT	1.880	9.900	8.503	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
FIAT	FD30		UNSEALED	2.036	11.660	9.042	B3815	A3541	30	25551	50-008-002	50-007-001	32	915016
FIAT	FD30		SALT	2.036	11.650	9.035	B3815	A3541	30	25551	50-008-002	50-007-001	32	915105
FIAT	FD31		SEALED	2.373	12.950	11.250	B3607/8	A3541	35	25553	50-020	50-021-2	35	915029
FIAT	FD31		SALT	2.373	12.950	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915094
FIAT	FD31		UNSEALED	2.375	12.950	11.250	B3607/8	A3541	35	25553	50-020	50-021-2	35	915073
FIAT	FD40		SALT	2.373	12.950	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915094
FIAT	FD40		UNSEALED	2.374	12.953	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915142
FIAT	FD40		SALT	2.374	12.953	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915221
FIAT	FD40		UNSEALED	2.375	12.950	11.250	B3607/8	A3541	35	25553	50-020	50-021-2	35	915073
FIAT	FD40B		UNSEALED	2.374	12.953	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915142
FIAT	FD40B		SALT	2.374	12.953	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915221
FIAT	FD5		UNSEALED	1.143	6.457	6.299	A3536	A3539	27	200281	50-008-002	50-007-006	27	915120
FIAT	FD5		SALT	1.260	6.420	6.299	A3537	A3539	27	25498	50-008-002	50-007-005	27	915130
FIAT	FD50		UNSEALED	2.622	14.000	11.281	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915218
FIAT	FD50		SALT	2.622	14.000	11.281	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915218
FIAT	FD7		UNSEALED	1.143	6.457	6.299	A3536	A3539	27	200281	50-008-002	50-007-006	27	915120
FIAT	FD7		SALT	1.260	6.420	6.299	A3537	A3539	27	25498	50-008-002	50-007-005	27	915130
FIAT	FD9		UNSEALED	1.382	7.170	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915014
FIAT	FD9		SALT	1.382	7.170	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915014
FIAT	FE16		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	FE20		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	FE20LC		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	FE8LC		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	FH120		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	FH150		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	FH150LC		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	FH200		SEALED	1.458	8.031	6.929	B3635	A3540	27	25500	50-008-002	50-007-004	27	915118
FIAT	FH200LC		SEALED	1.458	8.031	6.929	B3635	A3540	27	25500	50-008-002	50-007-004	27	915118
FIAT	FL10		UNSEALED	1.459	7.874	6.929	B3635	A3540	27	25500	50-008-002	50-007-004	27	915022
FIAT	FL10B		UNSEALED	1.459	7.874	6.929	B3635	A3540	27	25500	50-008-002	50-007-004	27	915022

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
FIAT	FL12		UNSEALED	1.578	8.661	7.480	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	FL14		SALT	1.577	8.660	6.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	FL14		UNSEALED	1.578	8.661	7.480	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	FL14B		UNSEALED	1.578	8.661	7.480	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	FL14C		UNSEALED	1.578	8.661	7.480	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	FL14D		SALT	1.577	8.660	6.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	FL14E		SALT	1.577	8.660	6.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915022
FIAT	FL20	S/N 7607 & DN	UNSEALED	1.873	9.843	8.504	B3815	A3541	30	25551	50-008-002	50-007-002	30	915019
FIAT	FL20	7608 & UP	SALT	1.880	9.900	8.503	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
FIAT	FL4		UNSEALED	0.868	5.118	4.921	A3536	A3539	27	25503	50-008-002	50-007-008	27	915316
FIAT	FL4	Berco	UNSEALED	0.984	5.354	5.512	A3536	A3539	27	200281	50-008-002	50-007-007	27	915046
FIAT	FL4AC		UNSEALED	0.984	5.280	5.512	A3536	A3539	27	200281	50-008-002	50-007-007	27	915028
FIAT	FL4AD		UNSEALED	0.984	5.280	5.512	A3536	A3539	27	200281	50-008-002	50-007-007	27	915028
FIAT	FL4L		UNSEALED	0.984	5.280	5.512	A3536	A3539	27	200281	50-008-002	50-007-007	27	915028
FIAT	FL5		UNSEALED	1.143	6.457	6.299	A3536	A3539	27	200281	50-008-002	50-007-006	27	915120
FIAT	FL5		SALT	1.260	6.420	6.299	A3537	A3539	27	25498	50-008-002	50-007-005	27	915130
FIAT	FL5B		SALT	1.260	6.420	6.299	A3537	A3539	27	25498	50-008-002	50-007-005	27	915130
FIAT	FL6		UNSEALED	1.181	6.100	6.299	A3536	A3539	27	25498	50-008-002	50-007-006	27	915027
FIAT	FL6	Berco	UNSEALED	1.181	6.102	6.299	A3536	A3539	27	25498	50-008-002	50-007-006	27	915170
FIAT	FL7		UNSEALED	1.143	6.457	6.299	A3536	A3539	27	200281	50-008-002	50-007-006	27	915120
FIAT	FL7		SALT	1.260	6.420	6.299	A3537	A3539	27	25498	50-008-002	50-007-005	27	915130
FIAT	FL7		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	FL7B		SALT	1.260	6.420	6.299	A3537	A3539	27	25498	50-008-002	50-007-005	27	915130
FIAT	FL8		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	FL8C		UNSEALED	1.377	7.010	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	FL9		UNSEALED	1.380	7.126	6.693	B3635	A3540	27	25499	50-008-002	50-007-004	27	915025
FIAT	FP120	S/N 41-3000	UNSEALED	2.374	12.953	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915142
FIAT	FP120	S/N 41-3000	SALT	2.374	12.953	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915221
FIAT	GH11E	S/N 10000 & DN	UNSEALED	1.565	8.140	7.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915214
FIAT	H3		UNSEALED	1.253	5.840	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915219
FIAT	H4		UNSEALED	1.250	6.240	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915004
FIAT	H4		UNSEALED	1.253	5.840	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915219
FIAT	HD10		UNSEALED	1.753	8.370	7.850	B3635	A3540	27	25548	50-008-002	50-007-002	27	915220
FIAT	HD11	S/N 7538-10000	SEALED	1.562	8.140	7.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915031
FIAT	HD11	S/N 1000 & DN	UNSEALED	1.565	8.140	7.006	B3635	A3540	27	25547	50-008-002	50-007-010	27	915023
FIAT	HD11	S/N 10001 & UP	UNSEALED	1.620	8.400	7.006	B3635	A3540	27	25547	50-008-002	50-007-003	27	915024
FIAT	HD11	SN 5901 & UP	SEALED	1.620	8.400	7.006	B3635	A3540	27	25547	50-008-002	50-007-003	27	915024
FIAT	HD11B		SEALED	1.620	8.400	7.006	B3635	A3540	27	25547	50-008-002	50-007-003	27	915024
FIAT	HD11B	S/N 10001-19484	UNSEALED	1.620	8.400	7.006	B3635	A3540	27	25547	50-008-002	50-007-003	27	915024
FIAT	HD11B	S/N 19485 & UP	UNSEALED	1.620	8.600	7.006	B3635	A3540	27	25547	50-008-002	50-007-003	27	915215
FIAT	HD11E	S/N 10000 & DN	SEALED	1.565	8.140	7.006	B3635	A3540	27	25547	50-008-002	50-007-010	27	915023
FIAT	HD11G	S/N 8940 & DN	SEALED	1.565	8.140	7.006	B3635	A3540	27	25547	50-008-002	50-007-010	27	915023
FIAT	HD11G	S/N 8940 & DN	UNSEALED	1.565	8.140	7.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915214
FIAT	HD11G	S/N 8940 & UP	UNSEALED	1.565	8.140	7.006	B3635	A3540	27	25547	50-008-002	50-007-010	27	915023
FIAT	HD14		UNSEALED	1.875	9.670	7.850	B3815	A3541	30	25551	50-008-002	50-007-002	30	915020

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
FIAT	HD15		UNSEALED	1.753	9.330	7.858	B3635	A3540	27	25548	50-008-002	50-007-002	27	915021
FIAT	HD16	S/N 5900 & DN	UNSEALED	1.753	9.330	7.858	B3635	A3540	27	25548	50-008-002	50-007-002	27	915021
FIAT	HD16	S/N 5901 & UP	UNSEALED	1.874	10.270	7.858	B3815	A3541	30	25551	50-008-002	50-007-002	30	915020
FIAT	HD16	S/N 5901 & UP	SEALED	1.876	10.270	7.850	B3815	A3541	30	25551	50-008-002	50-007-002	30	915020
FIAT	HD16B		SEALED	1.878	10.270	7.858	B3815	A3541	30	25551	50-008-002	50-007-002	30	915030
FIAT	HD19		UNSEALED	1.876	11.660	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915217
FIAT	HD19		SEALED	1.876	11.660	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915017
FIAT	HD19		SEALED	1.878	11.660	9.008	B3815	A3541	30	25551	50-008-002	50-007-002	32	915017
FIAT	HD20		UNSEALED	1.876	11.660	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915217
FIAT	HD20		SEALED	1.876	11.660	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915017
FIAT	HD20		SEALED	1.878	11.660	9.008	B3815	A3541	30	25551	50-008-002	50-007-002	32	915017
FIAT	HD21	S/N14943 & UP	UNSEALED	1.878	11.660	9.008	B3815	A3541	30	25551	50-008-002	50-007-002	32	915017
FIAT	HD21	S/N 13871-14942	SEALED	1.878	11.660	9.008	B3815	A3541	30	25551	50-008-002	50-007-002	32	915017
FIAT	HD21	S/N 14942 & DN	UNSEALED	1.878	11.660	9.008	B3815	A3541	30	25551	50-008-002	50-007-002	32	915221
FIAT	HD21	S/N14943 & UP	SEALED	1.878	11.660	9.008	B3815	A3541	30	25551	50-008-002	50-007-002	32	915017
FIAT	HD21B		UNSEALED	1.876	11.660	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915018
FIAT	HD21B		SEALED	1.876	11.660	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915016
FIAT	HD21C		UNSEALED	2.036	11.660	9.042	B3815	A3541	30	25551	50-008-002	50-007-001	32	915016
FIAT	HD21P	S/N 14942 & DN	UNSEALED	1.876	11.660	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915217
FIAT	HD21P	S/N 14942 & DN	SEALED	1.876	11.660	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915017
FIAT	HD21P	S/N 14943 & UP	UNSEALED	1.878	11.660	9.008	B3815	A3541	30	25551	50-008-002	50-007-002	32	915017
FIAT	HD3		UNSEALED	1.253	5.840	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915219
FIAT	HD31		SALT	2.373	12.950	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915094
FIAT	HD31		UNSEALED	2.375	12.950	11.250	B3607/8	A3541	35	25553	50-020	50-021-2	35	915073
FIAT	HD4	S/N 3001 & UP	UNSEALED	1.250	6.240	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915004
FIAT	HD4		UNSEALED	1.253	5.840	6.000	A3537	A3539	27	25498	50-008-002	50-007-005	27	915219
FIAT	HD41		SEALED	2.373	12.950	11.250	B3607/8	A3541	35	25553	50-020	50-021-2	35	915029
FIAT	HD41		SALT	2.373	12.950	11.281	B3607/8	A3541	35	25553	50-020	50-021-2	35	915094
FIAT	HD41		UNSEALED	2.375	12.950	11.250	B3607/8	A3541	35	25553	50-020	50-021-2	35	915073
FIAT	HD41B		SALT	2.622	14.000	11.280	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915218
FIAT	HD41B		UNSEALED	2.623	14.000	11.280	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915033
FIAT	HD5		UNSEALED	1.375	6.910	6.495	B3635	A3540	27	25499	50-008-002	50-007-004	27	915014
FIAT	HD5		SEALED	1.375	6.910	6.495	B3635	A3540	27	25499	50-008-002	50-007-004	27	915014
FIAT	HD5		UNSEALED	1.753	8.370	7.850	B3635	A3540	27	25548	50-008-002	50-007-002	27	915220
FIAT	HD50		UNSEALED	1.753	8.370	7.850	B3635	A3540	27	25548	50-008-002	50-007-002	27	915220
FIAT	HD50		SALT	2.622	14.000	11.280	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915218
FIAT	HD50		UNSEALED	2.623	14.000	11.280	B3631/2	A3541-001	35	25553	50-020	50-021-3	35	915033
FIAT	HD6		UNSEALED	1.375	6.910	6.495	B3635	A3540	27	25499	50-008-002	50-007-004	27	915014
FIAT	HD6		SEALED	1.375	6.910	6.495	B3635	A3540	27	25499	50-008-002	50-007-004	27	915014
FIAT	HD7	S/N 1102 & DN	UNSEALED	1.738	7.510	6.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915026
FIAT	HD7	S/N 1103 & UP	UNSEALED	1.565	8.140	6.500	B3635	A3540	27	25547	50-008-002	50-007-010	27	915023
FIAT	HD7G		SEALED	1.565	8.140	7.006	B3635	A3540	27	25547	50-008-002	50-007-010	27	915023
FIAT	HD7G		UNSEALED	1.565	8.140	7.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915214
FIAT	HD7G		UNSEALED	1.565	8.140	7.006	B3635	A3540	27	25547	50-008-002	50-007-010	27	915023
FIAT	HD7G-B		SEALED	1.562	8.140	7.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915031

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
FIAT	HD9		UNSEALED	1.565	8.140	7.000	B3635	A3540	27	25547	50-008-002	50-007-010	27	915214
FIAT	HD9		SEALED	1.565	8.140	7.006	B3635	A3540	27	25547	50-008-002	50-007-010	27	915023
FIAT	K		UNSEALED	1.738	7.510	6.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915026
FIAT	KO		UNSEALED	1.738	7.510	6.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915026
FIAT	PH130		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	S11		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	S9		SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	SL11	33/281 & UP	SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
FIAT	SL9	30/241 & UP	SEALED	1.377	7.165	6.692	B3635	A3540	27	25499	50-008-002	50-007-004	27	915154
HITACHI	EX100		UNSEALED	1.315	7.283	6.736	A3537	A3540	27	25499	50-008-002	50-007-005	27	915223
HITACHI	EX1100		SEALED	2.290	12.578	10.250	B3607/8	A3541	35	25553	50-020	50-021-2	35	915171
HITACHI	EX120		UNSEALED	1.315	7.283	6.736	A3537	A3540	27	25499	50-008-002	50-007-005	27	915223
HITACHI	EX1200-5		SEALED	2.290	12.578	10.250	B3607/8	A3541	35	25553	50-020	50-021-2	35	915171
HITACHI	EX1200-6	Berco KM2346	SEALED	2.362	12.772	11.023	B3607/8	A3541	35	25553	50-020	50-021-2	35	915339
HITACHI	EX150		SEALED	1.378	7.598	6.750	B3635	A3540	27	25499	50-008-002	50-007-004	27	915002
HITACHI	EX200		SEALED	1.442	8.346	7.484	B3635	A3540	27	25500	50-008-002	50-007-004	27	915134
HITACHI	EX220		SEALED	1.496	8.346	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915042
HITACHI	EX300		SEALED	1.750	9.650	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
HITACHI	EX400		SEALED	1.875	10.000	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
HITACHI	EX550		SEALED	1.909	11.570	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915087
HITACHI	EX700		SEALED	2.185	12.610	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
HITACHI	EX800		SEALED	2.185	12.610	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
HITACHI	EX90		UNSEALED	1.315	7.283	6.736	A3537	A3540	27	25499	50-008-002	50-007-005	27	915223
HITACHI	UH083		SALT	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
HITACHI	ZX350		SEALED	1.750	9.650	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
HYUNDAI	R160LC-9			1.403		7.000	B3635	A3540	27	25499	50-008-002	50-007-004	27	
JCB	JS220		SALT	1.752	9.933	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915084
JCB	JS300		SALT	1.752	9.933	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915084
JCB	JS330		SALT	1.752	9.933	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915084
JCB	JS360		SALT	1.752	9.933	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915084
JOHN DEERE	50		SEALED	0.867	4.840	5.315	A3536	A3539	27	25503	50-008-002	50-007-008	27	915027
JOHN DEERE	70		SEALED	1.190	6.102	6.063	A3536	A3539	27	25498	50-008-002	50-007-006	27	915025
JOHN DEERE	80		SEALED	0.950	5.157	6.062	A3536	A3539	27	200281	50-008-002	50-007-007	27	915074
JOHN DEERE	110		SEALED	1.319	7.008	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
JOHN DEERE	120		SEALED	1.319	7.008	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
JOHN DEERE	135		SEALED	1.319	7.008	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
JOHN DEERE	230		SEALED	1.493	8.366	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915042
JOHN DEERE	291		SEALED	1.181	6.456	6.125	A3536	A3539	27	25498	50-008-002	50-007-006	27	915136
JOHN DEERE	350		FLUSH	1.192	5.470	5.749	A3536	A3539	27	25498	50-008-002	50-007-006	27	915065
JOHN DEERE	370		SEALED	1.873	10.000	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915087
JOHN DEERE	440		FLUSH	1.004	5.469	5.749	A3536	A3539	27	200281	50-008-002	50-007-007	27	915064
JOHN DEERE	450		RECESSED	1.376	6.080	6.290	B3635	A3540	27	25499	50-008-002	50-007-004	27	915056
JOHN DEERE	450		FLUSH	1.377	6.080	6.290	B3635	A3540	27	25499	50-008-002	50-007-004	27	915056
JOHN DEERE	490		RECESSED	1.320	6.970	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915074
JOHN DEERE	550		SEALED	1.376	6.200	6.290	B3635	A3540	27	25499	50-008-002	50-007-004	27	915074

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
JOHN DEERE	555		SEALED	1.376	6.200	6.290	B3635	A3540	27	25499	50-008-002	50-007-004	27	915074
JOHN DEERE	590	S/N 001787 & UP	SEALED	1.366	7.598	6.750	A3537	A3540	27	25499	50-008-002	50-007-004	27	915228
JOHN DEERE	655		SEALED	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	655		SALT	1.440	8.110	6.991	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	700		SALT	1.440	8.110	6.991	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	750		SEALED	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	750		SALT	1.440	8.110	6.991	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	755		SEALED	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	755		SALT	1.440	8.110	6.991	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	790		SEALED	1.496	8.580	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915022
JOHN DEERE	792		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
JOHN DEERE	850		SEALED	1.750	9.060	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915013
JOHN DEERE	855		SEALED	1.878	9.902	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915083
JOHN DEERE	855		SALT	1.881	9.882	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915006
JOHN DEERE	890		SEALED	1.878	9.902	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915083
JOHN DEERE	890		RECESSED	1.880	9.900	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915227
JOHN DEERE	990		SEALED	1.878	9.902	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915083
JOHN DEERE	1280	EXC		1.439	8.110	6.900	B3635	A3540	27	25500	50-008-002	50-007-004	27	915229
JOHN DEERE	2010	S/N 42000 & DN	FLUSH	1.004	5.469	5.749	A3536	A3539	27	200281	50-008-002	50-007-007	27	915064
JOHN DEERE	2010	S/N 42001 & UP	FLUSH	1.192	5.470	5.749	A3536	A3539	27	25498	50-008-002	50-007-006	27	915065
JOHN DEERE	1050C		SALT	2.000	10.310	8.500	B3815	A3541	30	25551	50-008-002	50-007-001	30	915172
JOHN DEERE	1050J		SALT	2.000	10.310	8.500	B3815	A3541	30	25551	50-008-002	50-007-001	30	915172
JOHN DEERE	1050K		SALT	1.878	9.921	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915102
JOHN DEERE	1050K	Snap Ring AT468536	SALT	1.878	9.921	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915324
JOHN DEERE	1150D		SALT	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915215
JOHN DEERE	1155D		SALT	1.440	8.110	6.678	B3635	A3540	27	25500	50-008-002	50-007-004	27	915215
JOHN DEERE	120 EXC		SEALED	1.300	7.240	6.960	A3537	A3539	27	25499	50-008-002	50-007-005	27	915059
JOHN DEERE	120C		SEALED	1.319	7.008	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
JOHN DEERE	160CLC		SEALED	1.493	8.340	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915252
JOHN DEERE	160LC		SEALED	1.493	8.366	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915042
JOHN DEERE	190E		SEALED	1.190	6.102	6.063	A3536	A3539	27	25498	50-008-002	50-007-006	27	915025
JOHN DEERE	200LC		SEALED	1.493	8.366	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915042
JOHN DEERE	230CLC		SEALED	1.496	8.583	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915023
JOHN DEERE	230LC		SEALED	1.493	8.366	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915042
JOHN DEERE	230LC		SEALED	1.496	8.583	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915023
JOHN DEERE	240D		SEALED	1.496	8.583	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915023
JOHN DEERE	250G	Recessed	SEALED	1.496	8.370	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915279
JOHN DEERE	270CLC		SEALED	1.760	9.520	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915162
JOHN DEERE	270LC		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
JOHN DEERE	290D		SEALED	1.181	6.456	6.125	A3536	A3539	27	25498	50-008-002	50-007-006	27	915136
JOHN DEERE	330CLC		SEALED	1.760	9.520	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915162
JOHN DEERE	330LC	EXC	SEALED	1.760	9.520	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915162
JOHN DEERE	350B		FLUSH	1.192	5.470	5.749	A3536	A3539	27	25498	50-008-002	50-007-006	27	915065
JOHN DEERE	350C		FLUSH	1.192	5.470	5.749	A3536	A3539	27	25498	50-008-002	50-007-006	27	915065
JOHN DEERE	350D		SEALED	1.192	5.380	5.749	A3536	A3539	27	25498	50-008-002	50-007-006	27	915027

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
JOHN DEERE	350G		SEALED	1.756	9.527	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915323
JOHN DEERE	350GLC	BERCO	SEALED	1.770	9.500	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	27	915273
JOHN DEERE	400G		SEALED	1.192	5.380	5.749	A3536	A3539	27	25498	50-008-002	50-007-006	27	915027
JOHN DEERE	420C		FLUSH	1.004	5.469	5.749	A3536	A3539	27	200281	50-008-002	50-007-007	27	915064
JOHN DEERE	450B		RECESSED	1.376	6.080	6.290	B3635	A3540	27	25499	50-008-002	50-007-004	27	915056
JOHN DEERE	450C		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	450C	S/N 216337 & DN	RECESSED	1.376	6.080	6.290	B3635	A3540	27	25499	50-008-002	50-007-004	27	915056
JOHN DEERE	450C	S/N 216338 & UP	SEALED	1.376	6.200	6.290	B3635	A3540	27	25499	50-008-002	50-007-004	27	915074
JOHN DEERE	450CLC		SEALED	1.873	10.000	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915087
JOHN DEERE	450D		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	450D		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	450E		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	450G		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	450G		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	450H		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	450H		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	450J		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	450J		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	450J	Max Life Undercarriage	SALT	1.310	7.240	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	450LC		SEALED	1.873	10.000	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915087
JOHN DEERE	455D		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	455G		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	455G		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	490D		SEALED	1.319	7.008	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
JOHN DEERE	490E		SEALED	1.330	6.700	6.730	A3537	A3540	27	25499	50-008-002	50-007-005	27	915166
JOHN DEERE	550A		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	550A		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	550B		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	550B		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	550G		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	550G		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	550H		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	550H		SEALED	1.259	6.358	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915046
JOHN DEERE	550J		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	550J	Max Life Undercarriage	SALT	1.310	7.240	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	550K		SALT	1.256	6.378	6.290	A3537	A3539	27	25498	50-008-002	50-007-005	27	915014
JOHN DEERE	550K	Max Life Undercarriage	SALT	1.310	7.240	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	555G		SALT	1.310	7.240	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	555G		SEALED	1.318	7.224	6.290	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	590D	S/N 1787 & UP	SEALED	1.366	7.598	6.750	A3537	A3540	27	25499	50-008-002	50-007-004	27	915142
JOHN DEERE	590D		SEALED	1.378	7.598	6.750	B3635	A3540	27	25499	50-008-002	50-007-004	27	915002
JOHN DEERE	650G		SALT	1.310	7.240	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	650G		SEALED	1.318	7.224	6.290	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	650H		SALT	1.310	7.240	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	650H		SEALED	1.318	7.224	6.290	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
JOHN DEERE	650J		SALT	1.310	7.240	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	650J		SEALED	1.318	7.224	6.290	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	650K		SALT	1.310	7.240	6.734	A3537	A3540	27	25499	50-008-002	50-007-005	27	915089
JOHN DEERE	650K	Max Life Undercarriage	SALT	1.310	7.386	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915269
JOHN DEERE	655B		SALT	1.440	8.110	6.991	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	690A		RECESSED	1.320	6.970	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915074
JOHN DEERE	690B		RECESSED	1.320	6.970	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915074
JOHN DEERE	690C		RECESSED	1.320	6.970	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915074
JOHN DEERE	690D		RECESSED	1.320	6.970	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915074
JOHN DEERE	690E		SEALED	1.437	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915079
JOHN DEERE	690ELC		SEALED	1.437	8.150	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915079
JOHN DEERE	693B		RECESSED	1.320	6.970	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915074
JOHN DEERE	693D		SEALED	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	700H	Link T70316 & T70317	SALT	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915270
JOHN DEERE	700J		SALT	1.440	8.110	6.991	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	700J	Link T70316 & T70317	SALT	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915270
JOHN DEERE	700J	Link T149070 & T149071	SALT	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915163
JOHN DEERE	700J	Max Life Undercarriage	SALT	1.440	8.620	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915272
JOHN DEERE	700K		SALT	1.440	8.110	6.991	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	700K	Max Life Undercarriage	SALT	1.440	8.620	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915272
JOHN DEERE	70D		SEALED	1.190	6.102	6.063	A3536	A3539	27	25498	50-008-002	50-007-006	27	915025
JOHN DEERE	750B		SEALED	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	750B		SALT	1.440	8.110	6.991	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	750C		SALT	1.437	8.125	7.480	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
JOHN DEERE	750J		SALT	1.496	9.390	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915080
JOHN DEERE	750J	Berco Extended Pin Boss	SALT	1.496	9.390	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915080
JOHN DEERE	750K		SALT	1.496	9.390	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915080
JOHN DEERE	750K	Berco Extended Pin Boss	SALT	1.496	9.390	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915080
JOHN DEERE	755A		SEALED	1.753	9.130	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915099
JOHN DEERE	755B		SEALED	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	755C		SEALED	1.750	9.060	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915013
JOHN DEERE	755C		SALT	1.753	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915106
JOHN DEERE	790D		SEALED	1.496	8.583	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915023
JOHN DEERE	790E		SEALED	1.493	8.366	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915042
JOHN DEERE	790ELC		SEALED	1.493	8.366	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915042
JOHN DEERE	792D		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
JOHN DEERE	80C		SEALED	0.950	5.157	6.062	A3536	A3539	27	200281	50-008-002	50-007-007	27	915074
JOHN DEERE	850B		SALT	1.753	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915106
JOHN DEERE	850B		SEALED	1.753	9.130	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915099
JOHN DEERE	850C		SEALED	1.750	9.060	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915013
JOHN DEERE	850C		SALT	1.753	9.060	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915106
JOHN DEERE	850J		SALT	1.750	10.315	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	30	915175
JOHN DEERE	850J	Berco Extended Pin Boss	SALT	1.750	10.315	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	30	915280
JOHN DEERE	850K		SALT	1.750	10.315	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	30	915175
JOHN DEERE	850K	Berco Extended Pin Boss	SALT	1.750	10.315	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	30	915280

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
JOHN DEERE	890A		SEALED	1.878	9.902	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915083
JOHN DEERE	892D		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
JOHN DEERE	892E		SEALED	1.750	9.646	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915121
JOHN DEERE	950J		SALT	1.870	10.860	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915189
JOHN DEERE	950K	Berco Extended Pin Boss	SALT	1.875	10.866	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915329
JOHN DEERE	992D		SEALED	1.873	10.000	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915087
JOHN DEERE	992E		SEALED	1.873	10.000	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915087
JOHN DEERE	EX120		SEALED	1.319	7.008	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
JOHN DEERE	EX120-2		SEALED	1.330	6.700	6.730	A3537	A3540	27	25499	50-008-002	50-007-005	27	915166
JOHN DEERE	EX150		SEALED	1.378	7.598	6.750	B3635	A3540	27	25499	50-008-002	50-007-004	27	915002
JOHN DEERE	JD700		SEALED	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	JD700HLGP		SEALED	1.440	8.110	6.909	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
JOHN DEERE	JD700HLGP		SALT	1.440	8.110	6.991	B3635	A3540	27	25500	50-008-002	50-007-004	27	915042
KOBELCO	K909A		UNSEALED	1.496	8.580	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915023
KOBELCO	SK135SR-2	Berco LK 49A	SEALED	1.313	7.008	6.750	A3537	A3540	27	25499	50-008-002	50-007-005	27	915140
KOMATSU	D120-15		SEALED	1.988	11.300	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915055
KOMATSU	D120-18		SEALED	1.988	11.300	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915055
KOMATSU	D120-8		SEALED	1.988	11.300	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915055
KOMATSU	D125-18		RECESSED	1.988	11.300	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915206
KOMATSU	D135A-1		SALT	1.909	11.575	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915087
KOMATSU	D150-1		SALT	1.909	11.570	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915055
KOMATSU	D150-1	S/N 6843 & UP	UNSEALED	1.929	11.535	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915086
KOMATSU	D150-1	S/N 6843 & UP	SEALED	1.929	11.540	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915086
KOMATSU	D150-1	S/N 6842 & DN	UNSEALED	1.988	11.299	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915055
KOMATSU	D150-1	S/N 6842 & DN	SEALED	1.988	11.300	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915055
KOMATSU	D155		SALT	1.909	11.570	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915055
KOMATSU	D155		SEALED	1.988	11.300	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915055
KOMATSU	D155-1		SALT	1.909	11.570	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915055
KOMATSU	D155-1	S/N 6843 & UP	UNSEALED	1.929	11.535	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915086
KOMATSU	D155-1	S/N 6843 & UP	SEALED	1.929	11.540	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915086
KOMATSU	D155-1	S/N 6842 & DN	SEALED	1.988	11.300	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915055
KOMATSU	D155-1	S/N 10263-19064	SEALED	1.907	11.575	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915087
KOMATSU	D155-1	S/N 19065 & UP	SALT	1.909	11.574	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915087
KOMATSU	D155-1	S/N 6842 & DN	UNSEALED	1.988	11.299	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915055
KOMATSU	D155A		SALT	1.909	11.570	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915055
KOMATSU	D155A-1	S/N 2540-10262	SEALED	1.909	11.300	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915055
KOMATSU	D155A-2		SEALED	1.909	11.480	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915087
KOMATSU	D155A-2		SALT	1.909	11.574	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915087
KOMATSU	D155A-5		SEALED	1.909	11.480	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915167
KOMATSU	D155AX-3		SEALED	1.909	11.480	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915167
KOMATSU	D155AX-5		SEALED	1.909	11.480	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915167
KOMATSU	D155AX-6		SALT	1.933	11.417	9.055	B3815	A3541	30	25551	50-008-002	50-007-002	32	915330
KOMATSU	D155AX-7		SALT	1.933	11.417	9.055	B3815	A3541	30	25551	50-008-002	50-007-002	32	915330
KOMATSU	D20		SALT	0.945	5.550	5.310	A3536	A3539	27	200281	50-008-002	50-007-007	27	915123
KOMATSU	D20		SEALED	0.945	5.630	5.310	A3536	A3539	27	200281	50-008-002	50-007-007	27	915124

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
KOMATSU	D21		SALT	0.945	5.550	5.310	A3536	A3539	27	200281	50-008-002	50-007-007	27	915123
KOMATSU	D21		SEALED	0.945	5.630	5.310	A3536	A3539	27	200281	50-008-002	50-007-007	27	915124
KOMATSU	D250		RECESSED	2.165	12.323	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915054
KOMATSU	D275A-2		SALT	2.240	12.610	10.250	B3607/8	A3541	35	25501	50-020	50-021-1	35	915063
KOMATSU	D275A-5		SALT	2.185	11.400	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	32	915063
KOMATSU	D275AX	Dual Bushing	SALT	2.070	11.430	10.250	B3815	A3541	30	25501	50-008-002	50-007-001	32	915093
KOMATSU	D275AX-5		SALT	2.240	11.360	10.250	B3607/8	A3541	35	25501	50-020	50-021-1	32	915063
KOMATSU	D30-15		SEALED	1.102	6.594	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915057
KOMATSU	D30A		SEALED	1.102	6.594	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915057
KOMATSU	D30S-1		SEALED	1.094	6.590	6.060	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D30S-15	S/N 5016 & UP	SEALED	1.102	6.594	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915057
KOMATSU	D31		UNSEALED	1.180	6.690	6.060	A3536	A3539	27	25498	50-008-002	50-007-006	27	915069
KOMATSU	D31-15		SEALED	1.102	6.594	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915057
KOMATSU	D31-16		SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D31-16		SEALED	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D31E		SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D31E-12		SEALED	1.102	6.594	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915057
KOMATSU	D31P		SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D31P		UNSEALED	1.180	6.690	6.060	A3536	A3539	27	25498	50-008-002	50-007-006	27	915069
KOMATSU	D31P-20		SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D31PL		SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D31PLL	S/N 29001 & UP	SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D31PX		SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D31S		SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D355		SALT	2.185	12.736	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915091
KOMATSU	D355		FLUSH	2.244	12.579	10.250	B3607/8	A3541	35	25501	50-020	50-021-1	35	915053
KOMATSU	D355A-1	S/N 1010-1631	SEALED	2.244	12.578	10.250	B3607/8	A3541	35	25501	50-020	50-021-1	35	915088
KOMATSU	D355A-3	S/N 4234 & UP	SALT	2.185	12.736	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915091
KOMATSU	D355A-3	S/N 1632-4233	SEALED	2.185	12.736	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915091
KOMATSU	D355A-5	S/N 4234 & UP	SALT	2.185	12.736	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915091
KOMATSU	D37		SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D375		SALT	2.240	12.610	10.250	B3607/8	A3541	35	25501	50-020	50-021-1	35	915063
KOMATSU	D375A-1		SALT	2.240	12.610	10.250	B3607/8	A3541	35	25501	50-020	50-021-1	35	915063
KOMATSU	D375A-2		SALT	2.360	12.770	11.040	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	D375A-3		SALT	2.360	12.770	11.040	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	D375A-5		SALT	2.362	12.770	11.040	B3607/8	A3541	35	25553	50-020	50-021-2	35	915165
KOMATSU	D375A-6		SALT	2.362	12.634	11.040	B3607/8	A3541	35	25553	50-020	50-021-2	35	915276
KOMATSU	D37P		SALT	1.102	6.693	6.063	A3536	A3539	27	200281	50-008-002	50-007-006	27	915058
KOMATSU	D39E		SALT	1.307	7.244	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915052
KOMATSU	D39EX		SALT	1.307	7.244	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915052
KOMATSU	D39P		SALT	1.307	7.244	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915052
KOMATSU	D39PX		SALT	1.307	7.244	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915052
KOMATSU	D40		SALT	1.377	7.130	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D40		SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D40		RECESSED	1.488	8.583	6.890	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059

Note: Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
KOMATSU	D40P-1	BERCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D41	NEW	SALT	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915122
KOMATSU	D41		SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D41		UNSEALED	1.499	8.660	6.890	B3635	A3540	27	25500	50-008-002	50-007-010	27	915122
KOMATSU	D41-6		SALT	1.307	7.244	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915052
KOMATSU	D41A	BERCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D41E	S/N 50201 & UP	SALT	1.307	7.224	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915067
KOMATSU	D41E		SALT	1.307	7.244	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915052
KOMATSU	D41P		SALT	1.307	7.244	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915052
KOMATSU	D41P	BERCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D41P-6	S/N 50201 & UP	SALT	1.307	7.224	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915067
KOMATSU	D41PX-12		SALT	1.432	7.845	6.875	B3635	A3540	27	25500	50-008-002	50-007-004	27	915163
KOMATSU	D41Q-3	BERCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D41S	BERCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D45		RECESSED	1.488	8.583	6.890	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D45A		SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915059
KOMATSU	D45A	S/N 12178+ BRCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D45B	S/N 12178+ BRCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D45P-1	S/N 1501 & UP	SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915059
KOMATSU	D50		SALT	1.377	7.130	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D50		SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D50		RECESSED	1.488	8.583	6.890	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D50-11		RECESSED	1.488	8.583	6.890	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D50-15		SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915059
KOMATSU	D50-15		RECESSED	1.488	8.583	6.890	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D50A	BERCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D50B	S/N 10901+ BRCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D50P	S/N 10901+ BRCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D50S	S/N 10901+ BRCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D50S-11		RECESSED	1.488	8.583	6.890	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D51EX-22 / PX-22		SALT	1.425	8.661	6.901	B3635	A3540	27	25500	50-008-002	50-007-004	27	915192
KOMATSU	D53	NEW	SALT	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915122
KOMATSU	D53		UNSEALED	1.499	8.660	6.890	B3635	A3540	27	25500	50-008-002	50-007-010	27	915122
KOMATSU	D53		SALT	1.377	7.130	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D53-15		SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915059
KOMATSU	D53-16		SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D53A	BERCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D53A-15	S/N 60001 & UP	SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915059
KOMATSU	D55		SEALED	1.496	8.661	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D55-S		RECESSED	1.488	8.583	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915056
KOMATSU	D57-1		SEALED	1.496	8.661	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D57-1		UNSEALED	1.500	8.660	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915233
KOMATSU	D57S-1		SEALED	1.496	8.661	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D58		SALT	1.377	7.130	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D58		SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
KOMATSU	D58E	BERCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D58P-1	BERCO	SEALED	1.496	8.661	6.906	B3635	A3540	27	25500	50-008-002	50-007-010	27	915059
KOMATSU	D6	S/N 50001-50200	SALT	1.307	7.244	6.750	A3537	A3539	27	25499	50-008-002	50-007-005	27	915052
KOMATSU	D60		SALT	1.750	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D60		SEALED	1.760	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D60-6		SEALED	1.752	9.260	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915062
KOMATSU	D60A	BERCO NON-OEM	SEALED	1.756	9.449	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915116
KOMATSU	D60-A		RECESSED	1.488	8.583	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915056
KOMATSU	D61		SALT	1.496	8.897	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D61E		SALT	1.496	8.897	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D61EX		SALT	1.496	8.897	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D61P		SALT	1.496	8.897	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D61PX		SALT	1.496	8.897	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D61PX-12		SALT	1.496	8.897	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D63E		SALT	1.377	7.130	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D63E		SEALED	1.382	7.170	6.890	B3635	A3540	27	25499	50-008-002	50-007-004	27	915060
KOMATSU	D65		SEALED	1.490	8.660	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	D65		SALT	1.750	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D65		SEALED	1.760	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D65-6	S/N 34001 & UP	SALT	1.756	9.528	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915097
KOMATSU	D65A	BERCO NON-OEM	SEALED	1.756	9.449	7.984	B3635	A3540	27	25548	50-008-002	50-007-002	27	915116
KOMATSU	D65A		SEALED	1.760	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D65E		SEALED	1.760	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D65EX-12		SALT	1.750	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D65EX-15		SALT	1.750	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D65P-6	S/N 20006 & UP	SEALED	1.760	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D65PX		SALT	1.750	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D65PX-12		SALT	1.750	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D65PX-15		SALT	1.750	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D66		SALT	1.756	9.528	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915097
KOMATSU	D66		SEALED	1.760	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D68		SALT	1.756	9.528	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915097
KOMATSU	D68		SEALED	1.760	9.433	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915084
KOMATSU	D75		SEALED	1.843	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D75		SALT	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D75-S		SEALED	1.850	9.842	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915015
KOMATSU	D80		SEALED	1.843	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D80		SALT	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D80-7		SEALED	1.752	9.842	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915013
KOMATSU	D80-8		SEALED	1.752	9.842	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915013
KOMATSU	D85		SEALED	1.771	9.842	8.504	B3635	A3540	27	25548	50-008-002	50-007-002	30	915085
KOMATSU	D85		SALT	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D85-18	S/N 26513 & DN	SEALED	1.850	10.000	8.500	B3635	A3541	27	25551	50-008-002	50-007-002	30	915232
KOMATSU	D85-18	S/N 26514 & UP	SALT	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D85A		SEALED	1.771	9.842	8.504	B3635	A3540	27	25548	50-008-002	50-007-002	30	915085

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
KOMATSU	D85A		SEALED	1.843	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D85A-12		SEALED	1.850	9.842	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915015
KOMATSU	D85E		SEALED	1.843	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D85E-12	S/N 10001 & UP	SEALED	1.771	9.842	8.504	B3635	A3540	27	25548	50-008-002	50-007-002	30	915085
KOMATSU	D85E-12		SEALED	1.771	9.842	8.504	B3635	A3540	27	25548	50-008-002	50-007-002	30	915085
KOMATSU	D85EX-15		SALT	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D85P-18		SEALED	1.843	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D85PX		SALT	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D85PX-15		SALT	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D95		SALT	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D95		SEALED	1.843	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	D95-S		SEALED	1.772	10.000	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915232
KOMATSU	PC100		UNSEALED	1.180	6.690	6.060	A3536	A3539	27	25498	50-008-002	50-007-006	27	915069
KOMATSU	PC100		SEALED	1.180	6.810	6.890	A3536	A3539	27	25498	50-008-002	50-007-006	27	915161
KOMATSU	PC100	PITCH ALSO 6.89	SEALED	1.181	6.811	6.063	A3536	A3539	27	25498	50-008-002	50-007-006	27	915126
KOMATSU	PC1000		SEALED	2.244	12.614	10.250	B3607/8	A3541	35	25501	50-020	50-021-1	35	915063
KOMATSU	PC1000-1		SALT	2.240	12.610	10.250	B3607/8	A3541	35	25501	50-020	50-021-1	35	915063
KOMATSU	PC1000SE-1		SALT	2.240	12.610	10.250	B3607/8	A3541	35	25501	50-020	50-021-1	35	915063
KOMATSU	PC100-1		SEALED	1.181	6.535	6.062	A3536	A3539	27	25498	50-008-002	50-007-006	27	915110
KOMATSU	PC100-2		SEALED	1.181	6.535	6.062	A3536	A3539	27	25498	50-008-002	50-007-006	27	915110
KOMATSU	PC100-3		SEALED	1.181	6.535	6.062	A3536	A3539	27	25498	50-008-002	50-007-006	27	915110
KOMATSU	PC100-6		SEALED	1.180	6.810	6.890	A3536	A3539	27	25498	50-008-002	50-007-006	27	915161
KOMATSU	PC100L-6		SEALED	1.490	8.660	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	PC1100-6		UNSEALED	2.360	12.770	11.030	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	PC1100LC-6		UNSEALED	2.360	12.770	11.030	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	PC1100SP-6		UNSEALED	2.360	12.770	11.030	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	PC120		SEALED	1.180	6.810	6.890	A3536	A3539	27	25498	50-008-002	50-007-006	27	915161
KOMATSU	PC120	PITCH ALSO 6.89	SEALED	1.181	6.811	6.063	A3536	A3539	27	25498	50-008-002	50-007-006	27	915126
KOMATSU	PC120-1		SEALED	1.181	6.535	6.062	A3536	A3539	27	25498	50-008-002	50-007-006	27	915110
KOMATSU	PC120-2		SEALED	1.181	6.535	6.062	A3536	A3539	27	25498	50-008-002	50-007-006	27	915110
KOMATSU	PC120-3		SEALED	1.181	6.535	6.062	A3536	A3539	27	25498	50-008-002	50-007-006	27	915110
KOMATSU	PC120-6		SEALED	1.181	6.811	6.890	A3536	A3539	27	25498	50-008-002	50-007-006	27	915126
KOMATSU	PC120-6		SEALED	1.181	6.811	6.900	A3536	A3539	27	25498	50-008-002	50-007-006	27	915231
KOMATSU	PC120LC-6		SEALED	1.180	6.810	6.890	A3536	A3539	27	25498	50-008-002	50-007-006	27	915161
KOMATSU	PC1250		UNSEALED	2.360	12.770	11.030	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	PC1250-7		UNSEALED	2.360	12.770	11.030	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	PC1250LC-7		UNSEALED	2.360	12.770	11.030	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	PC1250LC-8		UNSEALED	2.360	12.770	11.030	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	PC1250SP-7		UNSEALED	2.360	12.770	11.030	B3607/8	A3541	35	25553	50-020	50-021-2	35	915131
KOMATSU	PC130-6		SEALED	1.180	6.810	6.890	A3536	A3539	27	25498	50-008-002	50-007-006	27	915161
KOMATSU	PC138		SEALED	1.180	6.810	6.890	A3536	A3539	27	25498	50-008-002	50-007-006	27	915161
KOMATSU	PC150		UNSEALED	1.499	8.660	6.890	B3635	A3540	27	25500	50-008-002	50-007-010	27	915122
KOMATSU	PC160LC-8		SEALED	1.496	8.346	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915108
KOMATSU	PC200		SEALED	1.496	8.661	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	PC200-6		SEALED	1.496	8.661	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060

Note: Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
KOMATSU	PC200-7		SEALED	1.496	8.661	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	PC200-8		SEALED	1.496	8.661	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	PC200-8MO		SEALED	1.496	8.346	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915277
KOMATSU	PC200LC-8		SEALED	1.496	8.346	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915108
KOMATSU	PC210LC-11		SEALED	1.503	8.346	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915193
KOMATSU	PC220		SEALED	1.496	8.661	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	PC240LC-10		SEALED	1.496	8.346	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915108
KOMATSU	PC240LC-6		SEALED	1.496	8.661	7.480	B3635	A3540	27	25500	50-008-002	50-007-010	27	915060
KOMATSU	PC240LC-8		SEALED	1.496	8.346	7.490	B3635	A3540	27	25500	50-008-002	50-007-010	27	915108
KOMATSU	PC250LC-6		SEALED	1.750	9.520	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915159
KOMATSU	PC270LC-6		SEALED	1.750	9.520	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915159
KOMATSU	PC270LC-7		SEALED	1.750	9.520	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915159
KOMATSU	PC270LC-8		SEALED	1.756	9.528	8.516	B3635	A3540	27	25548	50-008-002	50-007-002	30	915097
KOMATSU	PC290LC-10		SEALED	1.756	9.528	8.516	B3635	A3540	27	25548	50-008-002	50-007-002	30	915097
KOMATSU	PC300	EXC	SALT	1.750	9.530	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915097
KOMATSU	PC300	EXC	SEALED	1.760	9.530	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915076
KOMATSU	PC300-5		SEALED	1.748	9.527	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	30	915248
KOMATSU	PC300HD-6		SEALED	1.850	9.920	9.000	B3635	A3541	27	25551	50-008-002	50-007-002	30	915160
KOMATSU	PC300HD-8		SEALED	1.850	9.921	9.012	B3635	A3541	27	25551	50-008-002	50-007-002	30	915092
KOMATSU	PC300LC-6		SEALED	1.750	9.520	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915159
KOMATSU	PC300LC-7		SEALED	1.750	9.520	8.500	B3635	A3540	27	25548	50-008-002	50-007-002	30	915159
KOMATSU	PC300LC-8		SEALED	1.756	9.528	8.516	B3635	A3540	27	25548	50-008-002	50-007-002	30	915097
KOMATSU	PC350HD-8		SEALED	1.850	9.921	9.012	B3635	A3541	27	25551	50-008-002	50-007-002	30	915092
KOMATSU	PC350LC-8		SEALED	1.756	9.528	8.516	B3635	A3540	27	25548	50-008-002	50-007-002	30	915097
KOMATSU	PC360LC-10		SEALED	1.761	9.528	8.504	B3635	A3540	27	25548	50-008-002	50-007-002	30	915097
KOMATSU	PC390LC-10		SEALED	1.850	9.921	9.012	B3635	A3541	27	25551	50-008-002	50-007-002	30	915092
KOMATSU	PC-400 EX		SEALED	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915232
KOMATSU	PC400-3		SEALED	1.843	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	PC400-5		SEALED	1.843	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	PC400-6		SEALED	1.850	10.000	9.000	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	PC400-6		SEALED	1.843	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	PC400LC-7		SEALED	1.850	10.000	9.000	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	PC400LC-8		SEALED	1.850	9.921	9.012	B3635	A3541	27	25551	50-008-002	50-007-002	30	915092
KOMATSU	PC400LCSE-7		SEALED	1.850	10.000	9.000	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	PC450		SEALED	1.850	10.000	9.000	B3635	A3541	27	25551	50-008-002	50-007-002	30	915096
KOMATSU	PC450LC-8		SEALED	1.850	9.210	9.012	B3635	A3541	27	25551	50-008-002	50-007-002	27	915092
KOMATSU	PC490LC-10		SEALED	1.926	10.157	9.012	B3815	A3541	30	25551	50-008-002	50-007-002	30	915167
KOMATSU	PC60	EXC	SEALED	0.945	5.550	5.310	A3536	A3539	27	200281	50-008-002	50-007-007	27	915123
KOMATSU	PC600		SEALED	2.185	12.614	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
KOMATSU	PC600	EXC	SEALED	1.850	10.000	8.504	B3635	A3541	27	25551	50-008-002	50-007-002	30	915232
KOMATSU	PC600-6		SEALED	1.920	11.410	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915177
KOMATSU	PC600-7		SEALED	1.920	11.410	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915177
KOMATSU	PC600-8		SEALED	1.953	11.417	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915177
KOMATSU	PC600LC-6		SEALED	1.920	11.410	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915177
KOMATSU	PC600LC-7		SEALED	1.920	11.410	9.000	B3815	A3541	30	25551	50-008-002	50-007-002	32	915177

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
KOMATSU	PC650-5		SEALED	2.185	12.614	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
KOMATSU	PC700		SEALED	2.185	12.614	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
KOMATSU	PC710		SEALED	2.185	12.614	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
KOMATSU	PC75	Berco KM3041A	SEALED	0.945	5.157	6.063	A3536	A3539	27	200281	50-008-002	50-007-007	27	915180
KOMATSU	PC750		UNSEALED	2.200	12.610	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
KOMATSU	PC750SE-6		SEALED	2.185	12.614	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
KOMATSU	PC80	PITCH ALSO 6.89	SEALED	1.181	6.811	6.063	A3536	A3539	27	25498	50-008-002	50-007-006	27	915126
KOMATSU	PC800		SEALED	2.185	12.614	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
KOMATSU	PC80-1		SEALED	1.181	6.535	6.062	A3536	A3539	27	25498	50-008-002	50-007-006	27	915110
KOMATSU	PC80-3		SEALED	1.181	6.535	6.062	A3536	A3539	27	25498	50-008-002	50-007-006	27	915110
KOMATSU	PC850-8R1		SEALED	2.177	12.614	10.250	B3607/8	A3541	35	25501	50-008-002	50-007-001	35	915125
KUBOTA	KH170L	EXC	UNSEALED	0.994	5.510	5.310	A3536	A3539	27	200281	50-008-002	50-007-007	27	915040
LIEBHERR	631	MAY WORK	SALT	1.752	9.060	6.735	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
LIEBHERR	PR711		SALT	1.315	7.220	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915052
LIEBHERR	PR721		SALT	1.442	8.120	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915052
LIEBHERR	PR731		SALT	1.752	9.060	7.985	B3635	A3540	27	25548	50-008-002	50-007-002	27	915003
LIEBHERR	R912		SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
LIEBHERR	R922		SEALED	1.314	7.000	6.735	A3537	A3540	27	25499	50-008-002	50-007-005	27	915002
LIEBHERR	R932		SEALED	1.442	8.130	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
LINKBELT	LS2800		SEALED	1.442	8.130	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
LINKBELT	LS4800		SEALED	1.878	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
LINKBELT	LS5400		SEALED	1.878	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
LINKBELT	LS5800		SEALED	1.878	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915012
LINKBELT	LS6400		SEALED	2.003	11.440	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915001
LINKBELT	LS7400		SEALED	2.003	11.440	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915001
LINKBELT	LS7800		SEALED	1.442	8.130	6.735	B3635	A3540	27	25500	50-008-002	50-007-004	27	915009
LINKBELT	LS9800		SEALED	1.752	9.880	7.985	B3635	A3540	27	25548	50-008-002	50-007-002	30	915012
MASY.-FERG.	MF200B		SEALED	1.063	5.750	5.512	A3536	A3539	27	200281	50-008-002	50-007-007	27	915004
MASY.-FERG.	MF2244		RECESSED	0.984	5.420	5.512	A3536	A3539	27	200281	50-008-002	50-007-007	27	915057
MASY.-FERG.	MF300		RECESSED	1.299	6.610	6.299	A3537	A3539	27	25498	50-008-002	50-007-005	27	915002
MASY.-FERG.	MF300		SEALED	1.299	6.610	6.299	A3537	A3539	27	25498	50-008-002	50-007-005	27	915078
MASY.-FERG.	MF400C		SEALED	1.380	7.010	6.690	B3635	A3540	27	25499	50-008-002	50-007-004	27	915078
MASY.-FERG.	MF450		RECESSED	1.299	6.610	6.299	A3537	A3539	27	25498	50-008-002	50-007-005	27	915002
MASY.-FERG.	MF500		RECESSED	1.378	7.170	6.690	B3635	A3540	27	25499	50-008-002	50-007-004	27	915080
MASY.-FERG.	MF500B		SEALED	1.441	8.110	6.750	B3635	A3540	27	25500	50-008-002	50-007-004	27	915079
MASY.-FERG.	MF600C		SEALED	1.752	8.660	7.980	B3635	A3540	27	25548	50-008-002	50-007-002	27	915081
MASY.-FERG.	MFD400C		SEALED	1.380	7.010	6.690	B3635	A3540	27	25499	50-008-002	50-007-004	27	915078
MASY.-FERG.	MFD700C		SEALED	1.880	9.880	8.500	B3815	A3541	30	25551	50-008-002	50-007-002	30	915062
MTECK	825E	DRAGLINE	UNSEALED	2.381	12.181	11.023	B3607/8	A3541	32	25553	50-020	50-021-2	35	915353
TEREX	82-20AA,		RECESSED	1.750	9.190	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915075
TEREX	82-30		RECESSED	1.750	9.190	8.000	B3635	A3540	27	25548	50-008-002	50-007-002	27	915075
TEREX	82-30AA		RECESSED	1.750	11.520	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	32	915021
TEREX	82-30B		RECESSED	2.000	11.520	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915077
TEREX	82-30FA		RECESSED	1.750	11.520	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	32	915021
TEREX	82-40AA		RECESSED	1.750	11.520	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	32	915021

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)



WTC Machinery Corporation
MPP150 Tooling Chart

10/22/2025

TRACK TYPE				Track Dimensions			Disassembly Tools			Assembly Tools				
Make	Model	Comments	Type	Dia.	Length	Pitch	Pin Tool	Back Bushing	Rod Spacer Length	Forcing Pin	Track Pin Holder	Pin Adapter	Rod Spacer Length	PAT (x 2)
TEREX	82-40CA		RECESSED	1.750	11.520	8.000	B3635	A3540	30	25548	50-008-002	50-007-002	32	915021
TEREX	82-40DA		RECESSED	2.000	11.520	9.000	B3815	A3541	30	25551	50-008-002	50-007-001	32	915077
TEREX	82-50		RECESSED	2.380	12.380	10.312	B3607/8	A3541	35	25553	50-020	50-021-2	35	915063
TEREX	82-80DA		RECESSED	2.000	12.380	9.000	B3815	A3541	32	25551	50-008-002	50-007-001	35	915076
TEREX	TC-12		RECESSED	2.000	12.380	9.000	B3815	A3541	32	25551	50-008-002	50-007-001	35	915076
TIGER CAT	L870C			1.850	10.039	8.504	B3635	A3541	30	25551	50-008-002	50-007-002	30	915189
VOLVO	EC140BLCM		SEALED	1.457	8.366	7.512	B3635	A3540	27	25500	50-008-002	50-007-004	27	915106
VOLVO	EC150LC		SEALED	1.496	8.188	7.500	B3635	A3540	27	25500	50-008-002	50-007-010	27	915234
VOLVO	EC210BP		SEALED	1.457	8.693	7.512	B3635	A3540	27	25500	50-008-002	50-007-004	27	915189
VOLVO	EC330BLC		SEALED	1.854	10.016	8.500	B3635	A3541	30	25551	50-008-002	50-007-002	30	915092
VOLVO	EC460BLC		SEALED	1.878	11.417	8.540	B3815	A3541	30	25551	50-008-002	50-007-002	32	915260
VOLVO	EC480DL		SEALED	1.850	10.630	8.540	B3635	A3541	30	25551	50-008-002	50-007-002	30	915260
VOLVO	EC700CL		SEALED	2.228	12.598	10.240	B3607/8	A3541	35	25501	50-020	50-021-1	35	915261
VOLVO	ECR305C		SEALED	1.811	9.990	8.500	B3635	A3541	27	25551	50-008-002	50-007-002	30	915311
WIRTGEN	2100		RECESSED	1.327	7.250		A3537	A3540	27	25499	50-008-002	50-007-005	27	915272
WIRTGEN	2100		FLUSH	1.453	8.280		B3635	A3540	27	25500	50-008-002	50-007-004	27	915272

Note:Connecting Rod Spacers can be Cut in three Sections (27", 3" and 5") to Get Combined Tube Lengths of 27", 30" (27 + 3), 32" (27 + 5) and 35" (27 + 3 + 5)