



WTC MACHINERY Engineered to perform. Built to last.

WTC Machinery is a global leader in designing and building machinery and tooling for heavy equipment repair facilities.

AUTO LUBER

Overview

The Auto Luber tests and lubricates the track pin and bushing joints used on bulldozers, excavators and other crawler equipment.

This lubricator is used with either a 55 gallon or a 15 gallon drum oil reservoir. The reservoir and controls for the Lubricator are mounted on a mobile cart for portability. A small, light-weight handle attaches to the track chain allowing the track chains to be tested and lubricated immediately after assembly.

The one-button Automated Testing Cycle includes Pressure, Vacuum, and Fill Cycle Tests, with 10 second test vacuum and pressure tests for a thorough test of the track seals, and an easy to read display shows the progress of the testing and the results.



23-000 Auto Luber

Specifications:

Compressed Air Requirements -	80 – 120 psi (5,5 – 8,3 Bar) 4.0 scfm (0.06 m3/min)
Electrical Requirements -	120VAC 60 Hz 1-Phase - 9.7 Amps
	220VAC 50 Hz 1-Phase - 5.5 Amps
Dry Weight:	300 lbs (136 kg)

One (1) A2024 Blunt Needle is included with 23-000 Auto Luber

Additional/Optional Items

A2024	Blunt Needle -normally used for CAT track
A2679	Rounded Tip -small diameter normally used on JD and Komatsu track
A3334	Sharp Tip - normally used on seals that are self-sealing (Sorefa)
A3422	Shaft of needle has two diameters and an open tip
23-038	Optional Metering Handle, used to fill rollers and idlers to precise fluid levels.

23-000 Auto Lubricator - Specifications

The WTC Machinery Auto Lubricator is the easy, accurate way to test and lubricate crawler track chains.

DIMENSIONS

Weight (dry) -	300 lb (136 kg)	Width -	24 in (0,61 m)
Height -	51 in (1,29 m)	Length -	43 in (1,09 m)

ELECTRICAL

120VAC 60 Hz 1-Phase - 9.7 Amps
220VAC 50 Hz 1-Phase - 5.5 Amps

ELECTRICAL

40 – 120 psi (2,7 – 8,3 Bar) 4.0 scfm (0.06 m³/min)

CONTROLS

- Handle is small and light-weight with conveniently located controls
 - Track chains can be tested and lubricated immediately after assembly
 - Automated testing cycle includes: pressure, vacuum, and fill cycle tests, with 10 second vacuum and pressure tests
 - Works with 55 gallon or 15 gallon lubricant drums – no need to transfer lubricant to a separate tank
 - Mobile Cart makes filling rollers, idlers and other lubricating tasks possible
 - Strap heater keeps the lubricant at constant viscosity
- ***Optional metering handle is available for precise filling***

